



DLF/DLH2705-B

27" TFT LCD, 1000nits LED Backlight, 1920x1080

The **DLF/DLH2705-B** is a 27 inch industrial grade sunlight readable LCD, with high brightness 1000 nits, it produce sharp images, crisp text and lifelike colors. The Durapixel LED backlight technology ensures high reliability and low power consumption, suitable for outdoor application, kiosk, factory automation, military, transportation and gaming application.

Key Features

- High Brightness 1000 nits
- Sunlight Readable
- LED Backlight
- Low Power Consumption
- BL MTBF: 100,000 hours



Specifications

Model Name	DLF/DLH2705-B
Description	27" TFT LCD, 1000 nits LED Backlight, 1920x1080
Screen Size	27"
Display Area (mm)	597.888(H)x336.312(V)
Brightness	1000 cd/m ²
Resolution	1920x1080
Aspect Ratio	16 : 9
Contrast Ratio	1030 : 1
Pixel Pitch (mm)	0.3114(H)x0.3114(V)
Pixel Per Inch (PPI)	81
Viewing Angle	178°(H),178°(V)
Color Saturation (NTSC)	85%
Display Colors	16.7M
Response Time (Typical)	14ms
Panel Interface	LVDS
Input Interface	DVI-I, DP
Input Power	DC12V
Power Consumption	29W (31W with AD board)
OSD Key	4 Keys (Power Switch, Menu, +, -)
OSD Control	Brightness, Color, Contrast, Auto Turing, H/V Position...etc
Dimensions (mm)	611.50x355.80x13.50
Bezel Size(U/B/L/R)	6.773/12.694/6.806/6.806 mm
Weight (Net)	3.31kg
Operating Temperature	0 °C ~ 50 °C
Storage Temperature	-20 °C ~ 60 °C

DLF= Panel + LED Driving Board

DLH= Panel + LED Driving Board + AD Control Board

Specifications are subject to change without notice.

All brands or product names are trademarks or registered trademarks of their respective companies.








Mechanical Drawing

Outline Dimensions

Unit: mm





Connector View

Note :

1. THE DIMENSION EXCLUDES DEFORMATION.
2. I/F CONNECTOR TO BE JAE FI-X30H OR COMPATIBLE
3. M3 USER HOLE SCREW TORQUE 5.0 kgf·cm MAX.





Ordering Information

Part Number	Description
DLF2705-BNN-A11	27",1000nits,1920x1080,LID27B,5in1,V2
DLH2705-BNN-I11	27",1000nits,1920x1080,AD6038GDP+LID,DC12V,5in1,V2

Optional Accessories

Part Number	Description
840612051212	ADAPTER,AC/DC,12V/5 A,60W,Power-Din-4P,CWT,G99-ABF060F-N022,Efficiency-level-6,R
810618301010	CABLE,POWER,AC,1830mm USA type
810618301090	CABLE,POWER,AC,1830mm Europe type
810618301050	CABLE,POWER,AC,1830mm UK type
810618301170	CABLE,POWER,AC,1830mm Australia type
810618301031	CABLE,POWER,AC,1830mm Japan type

By Customer Request

Touch	PCT (Multi-Touch)
Glass	Tempered glass,AR coating.....

