Nano-Series Sub-THz Automated Tuners

DATA SHEET / 4T-050G11

MODELS: NT-110G-170G-1C NT-140G-220G-1C NT-170G-260G-1C NT-220G-330G-1C



ES France - Département RF & Hyperfréquences 127 rue de Buzenval BP 26 - 92380 Garches

 \bigcirc

C Tél. 01 47 95 99 60 Fax. 01 47 01 16 22

What is load pull?

Load Pull is the act of presenting a set of controlled impedances to a device under test (DUT) and measuring a set of parameters at each point. By varying the impedance, it is possible to fully characterize the performance of a DUT and use the data to:

- Verify simulation results of a transistor model (model validation)
- Gather characterization data for model extraction (behavioral model extraction)
- Design amplifier matching networks for optimum performance (amplifier design)
- Ensure a microwave circuit's ability to perform after being exposed to high mismatch conditions (ruggedness test)
- Confirm the stability or performance of a microwave circuit or consumer product under non-ideal VSWR conditions (stability/performance/ conformance/antenna test)

Example of load pull measurements with Output Power (Pout) contours plotted on a Smith Chart.



lso Pout Contours Measured @ 1.85 GHz



lso Pout Contours Simulated @ 1.85 GHz

Tél. 01 47 95 99 60 Fax. 01 47 01 16 22

Ċ

e-mail : hyper@es-france.com Site Web : www.es-france.com

 \bigcirc

Waveguide Impedance Tuner

One tool available to vary the impedances presented to a DUT is the waveguide impedance tuner. The tuner is based on a patented modified rectangular waveguide and a reflective vane or probe, sometimes referred to as a slug. Ideally, when the probe is fully retracted, the tuner presents a near 50Ω impedance at the DUT reference plane, represented by the center of a normalized Smith Chart. As the probe is lowered into the waveguide

(Y-direction) it interrupts the electric field, reflects some of the energy back towards the DUT and increases the magnitude of reflection (represented by the red curve on the Smith Chart at right.) As the probe travels along the waveguide (X-direction), the distance between the probe and the DUT is altered, thereby rotating the phase of the reflection (represented by the blue curve on the Smith Chart. It is therefore possible to present nearly any arbitrary impedance without the need of discrete components.



Patented Waveguide Tuner Architecture

U.S. PATENT NO. 5,910,754 INTERNATIONAL PATENTS PENDING

- Complex waveguide with perpendicular slots act as multichoke filter
- Complex waveguide with reduced height increases resonance-free bandwidth
- Non-conductive rectangular bar vane with metallized tip further isolates electric field



Tél. 01 47 95 99 60 Fax. 01 47 01 16 22

Pre-Calibration (Pre-Characterization)

Automated tuners have the ability to be pre-calibrated. Pre-calibration involves recording the s-parameters of the probe at varying X and Y positions for the frequencies of interest using a calibrated vector network analyzer. In general, X and Y positions are selected such that an even distribution of impedances are recorded over the Smith Chart. Once the calibration data is stored in a lookup table, the VNA is no longer required to use the tuner; the tuner 'knows' how to present impedances accurately without VNA verification.

Tuner Repeatability

Tuner repeatability is defined as the vector difference between the precalibrated s-parameter data and subsequent s-parameter measurements after movement, when returning the probe to a given X and Y position. Since the impedances presented to the DUT are reliant on the tuner's ability to accurately return to pre-calibrated states, repeatability is a critical tuner characteristic that affects the reliability of measurement data. In order to guarantee a high level of repeatability, precision mechanics and motors within the tuner are used to return the probe to its precalibrated positions with s-parameter vector differences of -50dB or better.

Tuning Accuracy and Interpolation

During pre-calibration, the tuner's s-parameters are recorded at a userdefinable number (normally between 300-3000) of X and Y positions giving an even distribution over the Smith Chart. However, an arbitrary load impedance that falls between pre-calibrated states might be required. To achieve a high level of accuracy, a two-dimensional algorithm is used to interpolate between the closest pre-calibrated impedances in order to determine the new physical X and Y positions of the desired interpolated impedance. Interpolation increases the number of tunable impedances well beyond the initial precalibration range.

Given a sufficiently dense pre-calibration look-up table, a tuner's repeatability (ability to return to pre-calibrated states) and accuracy (ability to interpolate between pre-calibrated states) offer similar performances.

Ċ



1

ES France - Département RF & Hyperfréquences 127 rue de Buzenval BP 26 - 92380 Garches Tél. 01 47 95 99 60 Fax. 01 47 01 16 22

Patented Tuner Controller

(U.S. Patent No. 8,823,392)

All Maury slide-screw automated impedance tuners are equipped with a patented controller (U.S. Patent No. 8,823,392) with onboard microprocessor and memory. After pre-calibration, the lookup table is copied onto the embedded flash memory storage, as are any s-parameter files of passive components that will be used with the tuner (adapters, cables, fixtures, probes, attenuators...). The onboard microprocessor will use the lookup table and component s-parameter blocks to calculate the probe positions required to present an arbitrary load impedance taking into account (de-embedding) all adapter/fixture losses between the

tuner and DUT, and all back-side losses between the tuner and the measurement instrument, as well as possible non- 50Ω terminations.

Tuner control settings including IP address and firmware upgrade.

Direct ASCII commands can be sent through raw TCP/IP interface over Ethernet or USB and used with any socket programming language or through any Telnet client program in any operating system. Commands include direct impedance tuning, reference-plane shifting, VSWR testing and more.

| Parameter | Value | | | | |
|-----------------------|-------------------------------------|--|--|--|--|
| Manufacturer | Maury Microwave Corporation | | | | |
| Instrument Model | MT982-EL30 | | | | |
| Serial Number | 5270 | | | | |
| Firmware Revision | 3.4-1.24 | | | | |
| Description | Maury MT982-EL30 - 5270 | | | | |
| LXI Extended Features | LXI Core Functions | | | | |
| LXI Version | 1.4 | | | | |
| mDNS-Hostname | 169.254.6.77, MT982-EL30-5270.local | | | | |
| IP Address | 169.254.6.77 | | | | |
| MAC Address | fc:6c:31:00:00:e6 | | | | |
| Device Address | TCPIP0::169.254.6.77::5025::SOCKET | | | | |
| Telnet Address | telnet://169.254.6.77:5024 | | | | |

| Parameter | Currently in use |
|---------------------|-------------------------|
| VXI-11 Discovery | On |
| mDNS Discovery | On |
| DHCP | On |
| Auto-IP | On |
| Network-Hostname | MT982-EL30-5270.local |
| IP Address | 169.254.6.77 |
| Netmask | 255.0.0.0 |
| Gateway | 0.0.0.0 |
| Dynamic DNS Updates | On |
| Manual DNS | Off |
| Domain | Belkin |
| Primary DNS | 10.10.1.17 |
| Secondary DNS | 10.10.1.19 |
| Description | Maury MT982-EL30 - 5270 |
| Web Password | hidden |

Edit Configuration

ES France - Département RF & Hyperfréquences 127 rue de Buzenval BP 26 - 92380 Garches Tél. 01 47 95 99 60 Fax. 01 47 01 16 22

MTUNE Tuner Characterization and Control Software

Introduction

MTUNE is a software package that allows device calibration/characterization and control of multiple tuner configurations for automated impedance tuning. It may be used in any application requiring the ability to match the impedance of a microwave circuit element or to establish specific impedances at a terminal interface at various frequencies. The software provides a standalone server (API) for remote communication for advanced use as well as interactive user interface to guide the user through the calibration and tuning process.

Software Features:

- > Desktop and cloud-based applications enhances user flexibility
- > Modern wizard-driven GUI with support for most commercial VNAs
- > Automatic instrument identification for easy setup
- > Stay up-to-date with software update reminders
- > Enhanced user support with direct ticketing and error logging

New and Updated Capabilities:

- > Faster multi-frequency tuner characterization
- > New tuner characterization validation process
- > Enhanced frequency interpolation
- > New non-harmonically related multi-frequency impedance tuning

MTUNE3 is compatible with all Nano-series tuners with embedded controllers, and can be downloaded from https://maurymw.com/



ES France - Département RF & Hyperfréquences 127 rue de Buzenval BP 26 - 92380 Garches Tél. 01 47 95 99 60 Fax. 01 47 01 16 22



Optimized for on-wafer integration

Nano-series automated impedance tuners have been optimized for on-wafer integration. The direct connection offers two advantages: maximizing VSWR at the DUT reference plane and minimizing phase skew at the DUT reference plane.



ies 🛞

Tél. 01 47 95 99 60 Fax. 01 47 01 16 22

Available Models

| Model | Frequency Range (GHz) | Matching Range | | - Powor | Vector | Insertion | | | |
|-----------------|-----------------------------|----------------|----------------------|--------------------------|----------------------------|--------------------------------|------------------|------------------|-------------|
| | | Minimum | Typical ¹ | Capability ² | Repeatability (Minimum) | Loss ³ (Maximum) | Dissipative Loss | Waveguide Flange | |
| NT-110G-170G-1C | 110-170 | 20:1 | 35:1 | 20 W CW, 200 W PEP | 20 W CW, | | 0.5 dB | -8 dB | WR6.5 (WR6) |
| NT-140G-220G-1C | 140-220 | 12:1 | 14:1 | | | | 0.65 dB | -4 dB | WR5.1 (WR5) |
| NT-170G-260G-1C | 170-260 | 18:1 | 27:1 | | -40.0 dB | 1 dB | -9 dB | WR4.3 (WR4) | |
| NT-220G-330G-1C | 220-330 | 12:1 | 17:1 | | | 1.35 dB | -8 dB | WR3.4 (WR3) | |

¹ Defined as average VSWR across the frequency band

² Power rated at maximum VSWR

³ With probes fully retracted

⁴ At maximum VSWR

Accessories Provided: > Power Supply

- > USB cable and TCPIP cable
- > USB to ethernet adapter
- > NT-1C Tuner controller
- > Operating Manual

Typical Performance

 \bigcirc



Tél. 01 47 95 99 60 Fax. 01 47 01 16 22

Ċ

VISIT OUR WEB STORE

OUR PRODUCTS





www.maurymw.com



ES France - Département RF & Hyperfréquences 127 rue de Buzenval BP 26 - 92380 Garches Tél. 01 47 95 99 60 Fax. 01 47 01 16 22

Maury Microwave

DATA SHEET / 4T-050G11 / 2024.10

© 2024 Maury Microwave. All Rights Reserved. Specifications are subject to change without notice. Maury Microwave is AS9100D & ISO 9001:2015 Certified.

CONTACT US:

W / maurymw.com E / maury@maurymw.com P / +1-909-987-4715 F / +1-909-987-1112 2900 Inland Empire Blvd Ontario, CA 91764



 \bigcirc

ES France - Département RF & Hyperfréquences 127 rue de Buzenval BP 26 - 92380 Garches Tél. 01 47 95 99 60 Fax. 01 47 01 16 22

5 99 60 1 16 22