

RFoF

RF duplexer, quadruple, bi-directional, 4 COM, 4 RF IN / OUT

RS-RFoF08-DUP

Properties

- Quadruple RF duplexer RFoF module: Includes RF duplexers and variable attenuators.
- Frequency range: 0.4 – 7.125 GHz.
- Adjustable RF attenuation: Software-controlled.
- Chassis compatibility: Fits 3RU CUBO chassis (9 slots) and 1RU CUBO chassis (2 slots).
- Hot swappable modules.
- CUBO rack NIC: Offers WebGUI, SNMP, and RESTCONF interface.



General data

Suitable products	RS-RFoF08-T13T15R2 , 85214842 RS-RFoF08-T13T15R2W, 85240467 RS-RFoF08-15T2R2W, 85252243 RS-RFoF08-13T2R2W, 85252241 RS-CH3U-0, 85095578 RS-MO-1, 85095577 RS-AC350-1, 85109107 RS-DC350-1, 85115711
Product family	RFoF Lab automation
Module type	modular line card system in 3RU and 1RU

RF data

Frequency range	400 MHz...7125 MHz
Minimum RF attenuation	
COM to RF IN	400 ... 6000 MHz
COM to RF IN	6000 ... 7125 MHz
COM to RF OUT	400 ... 6000 MHz
COM to RF OUT	6000 ... 7125 MHz
Attenuation range	0...30 dB
RF isolation RF IN – RF OUT	> 25 dB
RF return loss	RF return loss
	400 ... 6000 MHz
	6000 ... 7125 MHz
Maximum RF input power	+ 15 dBm



RFoF

RF duplexer, quadruple, bi-directional, 4 COM, 4 RF IN / OUT

RS-RFoF08-DUP

Electrical data	
Supply voltage (internal on backplane)	-48 DC
Power consumption	2.4 W
ESD rating	8 kV (contact voltage acc.to IEC 61000-4-2)

Mechanical data	
Dimensions (W x H x D)	37. x 110 x 187 mm
Weight	420 g
Mechanics	Compatible to CUBOchassis RS-CH3U-0 and RS-CH1U

Environmental data	
Operating temperature range (ambient Cubo chassis temperature)	-5 ... +45°C
Storage temperature	-40°C ... 85°C

Output of RF connections	
Product family RF connector	SMA
Gender	female
Amount of RF connectors	12 (4x COM, 4x RF IN, 4x RF OUT)


Management Parameter RF duplexers	
Not responding	alarm
Attenuation 1	configuration
Attenuation 2	configuration
Attenuation 3	configuration
Attenuation 4	configuration

Module Management Parameter	
Not responding	alarm
Card power supply failure	alarm
Temperature out of range	alarm
Part number (read only)	configuration
Firmware version (read only)	configuration
Serial number (read only)	configuration
Card assembly (read only)	configuration
Restore factory settings	configuration
Temperature	measurement
Current consumption	measurement




RFoF
RF duplexer, quadruple, bi-directional, 4 COM, 4 RF IN / OUT
RS-RFoF08-DUP

Block diagram



Reference Application



Order Information Table

Item number	Item description	Notes
85225216	RS-RFoF08-DUP	Lab automation, RF duplexer, quadruple, bi-directional, 4 COM, 4 RF IN, 4 RF OUT

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS.
Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT: DOC-0001298820 / Date of publication: 28.11.2024 / uncontrolled copy