

Multicoax breakout, 2x8, MXPM (male) to PC185 (female), 50 Ohm, 70 GHz, 152mm

MF53/2x8A_11MXPM/21PC185_e/152

Properties

- Operating range at up to 70 GHz
- Broadband characteristic
- Standard absolute phase matching down to ± 1 ps
- Highly flexible and ultra stable Multiflex cable
- 2.54 mm (0.1 inch) pitch centre-to-centre
- Magnetic locking mechanism
- Automatic interface protection
- Cost efficient PCB sockets



Product configuration

MULTICOAX assembly type	Breakout
Type of cable	MULTIFLEX_53-02
Type description connector A	2x8A_11_MXPM
Type description connector B	21_PC185
Length	152 mm
Length	6 inch
Length type	REF to REF

Electrical data

Impedance	50 Ω
Max. operating frequency	70 GHz

Environmental data

Operation temperature	0 °C ... 85 °C
-----------------------	----------------

Ordering information

Item number	Item description
85096261	MF53/2x8A_11MXPM/21PC185_e/152

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

HUBER+SUHNER



ES France - Département RF & Hyperfréquences
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 60
Fax. 01 47 01 16 22



e-mail : hyper@es-france.com
Site Web : www.es-france.com

Multicoax breakout, 2x8, MXPM (male) to PC185 (female), 50 Ohm, 70 GHz, 152mm
MF53/2x8A_11MXPM/21PC185_e/152

DOCUMENT PIM-P38247 / Date of publication: 09.09.2024 / uncontrolled copy

HYPER-SHUNED



ES France - Département RF & Hyperfréquences
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 60
Fax. 01 47 01 16 22



e-mail : hyper@es-france.com
Site Web : www.es-france.com