


AI Accelerator& GPU Preliminary

MXM Module MX5000B-XA




Features

- NVIDIA® RTX PRO™ 5000 Blackwell Embedded GPU
- 10,496 CUDA cores, 80 RT cores and 320 Tensor cores, 24GB GDDR7 memory
- PCIe Gen 4 x16 interface via golden finger
- 40.62 TFLOPS peak FP32 performance

Specifications

Model Number	MX5000B-XA	
GPU Engine Specs	NVIDIA RTX PRO 5000 Blackwell Embedded GPU Architecture: NVIDIA Blackwell CUDA Cores: 10,496 Tensor Cores: 320 RT Cores: 80 Floating Point Performance: 36.53 TFLOPS Core Clock (MHz): Base= 1095 / Boost= 1740	NVIDIA RTX PRO 5000 Blackwell Embedded GPU Architecture: NVIDIA Blackwell CUDA Cores: 10,496 Tensor Cores: 320 RT Cores: 80 Floating Point Performance: 40.62 TFLOPS Core Clock (MHz): Base= 1402 / Boost= 1935
Memory Specs	Size: 24GB GDDR7 Speed: 28 Gbps Interface Width: 256-bit Bandwidth (GB/sec): 896	
Feature Support	PCI Express 4.0 x16 DirectX: 12 Ultimate Open GL 4.6 Vulkan 1.2	
Display	Resolution: 7680x4320 ¹ Maximum resolution 8K@240Hz (7690x4320) Max: 4x DisplayPort 2.1a (DSC1.2a)	
Power Consumption	Total Graphics Power (TGP): 95 W @PWR_SRC 19V	Total Graphics Power (TGP): 115 W @PWR_SRC 19V
Form Factor	MXM Graphics Module Version 3.1, Type B	
Dimensions (WxD)	82.0 x 110.0 mm (3.22" x4.33")	
Net Weight	0.06 kg (0.1323 lb) (T.B.D.)	
Temperature	Standard: Operating Temp. :0 to + 55°C (32°F ~131°F) / Extended Operating Temp. : -40 to + 70°C (T.B.D.) / Storage Temperature: -40 to + 85°C (- 40°F ~ 185°F)	Standard: Operating Temp. :0 to + 55°C (32°F ~131°F) / Storage Temperature: -40 to + 85°C (- 40°F ~ 185°F)
Humidity	40°C @ 95%, Non-condensing	
OS Support	Windows 10-64bit / Windows 11 / Linux 64-bit	
Certification	CE/FCC/UKCA	

System & Mounting Dimensions



Product Specifications are subject to change without prior notice

Ordering Information

Model name	Description
MX5000B-XAA-A1	MXM-B, NVIDIA RTX PRO 5000 Blackwell, Gen4.0 x16, 24GB GDDR7, 4xDP, 115W, 0°C to +55°C
MX5000B-XAA-A2 (T.B.D.)	MXM-B, NVIDIA RTX PRO 5000 Blackwell, Gen4.0 x16, 24GB GDDR7, 4xDP, 95W, 0°C to +55°C

Accessory (Optional)

Part No.	Description
92-6MXM4H-1002	PCIe Carrier Board, MXM3.1, Gen4.0 x16, 4x HDMI, 0°C to +55°C
TBD	MXM-B Cooler, TWO BALL, 12V 4PIN