



## The Most **Reliable** Storage For Industries

ET130-eMMC



### Overview

Apacer ET130-eMMC is an embedded, non-volatile memory system that combines triple-level cell TLC NAND flash memory with an onboard eMMC controller, supporting the JEDEC Standard eMMC 5.1 interface. The integrated eMMC controller directly manages NAND flash media, freeing the host processor from various tasks, including ECC, wear-leveling, IOPS optimization, and read sensing.



ET130-eMMC serves as the ideal storage solution for a wide range of commercial applications, including digital TVs, set-top boxes, home automation, camera drones, body-worn cameras, AR/VR systems, wearable gadgets, electronic learning products, and more./ OR industrial applications, including embedded systems, factory automation, networking, transportation, aerospace and defense, surveillance, medical equipment, and more. Its compact BGA package sizes and minimal power consumption render eMMC an affordable and efficient memory solution for mobile and embedded products.

Offering capacities ranging from 16GB to 32GB within a JEDEC-compatible form factor, ET130-eMMC provides an excellent solution for vendors looking for seamless integration, a quick market entry, and ample storage capacity.



## Feature

- Variable clock frequencies of 0-200MHz
- Ten-wire bus interface with a hardware reset
- Supports three different data bus widths: 1 bit (default), 4 bits, and 8 bits
- Internal error correction code (ECC)
- Internal enhanced data management algorithm
- Power-loss data protection during programming operations.
- Secure bad block erase commands
- Enhanced write protection with permanent and partial options.
- Field firmware update (FFU)
- Device Health Report
- Pre EOL (End of Life) information
- Optimal size
- Production state awareness
- Power-off notification for sleep




## Specifications

|                                       |                                                                                                                                                      |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model                                 | ET130-eMMC                                                                                                                                           |
| Interface                             | eMMC5.1 HS400                                                                                                                                        |
| Form Factor                           | 153 Ball FBGA                                                                                                                                        |
| NAND Flash Type                       | TLC                                                                                                                                                  |
| Capacity                              | 16GB~32GB                                                                                                                                            |
| Sequential Read Performance (MB/sec)  | Up to 315                                                                                                                                            |
| Sequential Write Performance (MB/sec) | Up to 195                                                                                                                                            |
| Standard Operating Temperature ( °C ) | -25 ~ +85                                                                                                                                            |
| Storage Temperature ( °C )            | -40 ~ +85                                                                                                                                            |
| Thermal sensor                        | No                                                                                                                                                   |
| Operating Voltage                     | VCCQ=1.8V/3.3V<br>VCC = 3.3V                                                                                                                         |
| Power Consumption                     | Read: VCCQ(1.8V) = 160mA / VCC(3.3V) = 90mA<br>Write: VCCQ(1.8V) = 70mA / VCC(3.3V) = 60mA<br>Sleep Current: VCCQ(1.8V) = 0.1mA / VCC(3.3V) = 0.05mA |
| Dimension (L x W x H )                | 11.50 x 13.00 x 1.00 (mm)                                                                                                                            |



# Mechanical Specification



Unit: mm

For more information,  
contact your Apacer representative

Global Presence