



ENTERPRISE D-SERIES

Cloud-Scale Capacity Meets Gen5 Speed

PASCARI D201

Sequential Read

Up to 14,500 MB/s

Sequential Write

Up to 12,000 MB/s

Random Read

Up to 3,300K IOPS

Random Write

Up to 1,050K IOPS

Interface

PCIe 5.0 x4

Capacity

12.8 TB & 15.36 TB

Form Factor

E1.S 15mm

DWPD

1,3



Product Features

- NVMe 2.0d
- OCP Datacenter NVMe[®] SSD Specification V2.0
- OCP V2.6 Telemetry features
- 128 Namespaces
- Power Loss Protection (PLP)
- ISE, TCG Opal 2.02 support
- AES-XTS 256-bit Encryption
- Data Integrity and Protection
- End-to-End Data Path Protection
- SECDED
- Sanitize
- NVMe-MI (Management Interface) Rev 1.2
- SMBus



ES France - Mobilité & Systèmes Embarqués
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 80



e-mail : mse@es-france.com
Site Web : www.es-france.com

Solutions - D201E

Form Factor E1.S 15mm	
Capacity ⁽¹⁾	12.8 TB
Interface	PCIe 5.0 x4
NVMe	2.0d
NAND Flash	3D TLC
Performance ^(2,3)	
Sequential Read (MB/s)	14,500
Sequential Write (MB/s)	12,000
4K Random Read (IOPS)	3,300K
4K Random Write (IOPS)	1,050K
Power Consumption ⁽⁴⁾	
Active (W)	<25
Idle (W)	<5
Endurance/Reliability	
DWPD ⁽⁵⁾	3
UBER	< 1 sector per 10 ¹⁸ bits read
MTBF (million hours)	2.5
Limited Warranty (years)	5
Temperature	
Operating Temp. (°C)	0 - 70
Non-Operating Temp. (°C)	-40 - 85
Physical Dimension	
Length (mm)	118.75
Width (mm)	33.75
Height (mm)	15
Weight (g)	<100
Part Number	
ISE FW	DP20BH0812T8E3116T310
SED FW	DP20BH0812T8E2116T310
Non-SED FW	DP20BH0812T8E0116T310

(1) 1 TB = 10¹² bytes.

(2) Sequential Performance is based on FIO on Linux, 512KB data size, with QD=32, 1 job.

(3) Random Performance is based on FIO on Linux, 4KB data size, QD=128, 8 jobs.

(4) Power consumption (average RMS) is measured during the sequential read/write and random read/write operations performed by iometer with the conditions described in (2) and (3).

(5) The results of DWPD are obtained in compliance with JESD219A standards.



The data within this specification is subject to change by Phison without notice. Performance numbers may vary based on system configuration and testing conditions. Copyright © 2025 Phison Electronics. All rights reserved.



ES France - Mobilité & Systèmes Embarqués
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 80



e-mail : mse@es-france.com
Site Web : www.es-france.com

Solutions - D201P

Form Factor E1.S 15mm	
Capacity ⁽¹⁾	15.36 TB
Interface	PCIe 5.0 x4
NVMe	2.0d
NAND Flash	3D TLC
Performance ^(2,3)	
Sequential Read (MB/s)	14,500
Sequential Write (MB/s)	12,000
4K Random Read (IOPS)	3,300K
4K Random Write (IOPS)	600K
Power Consumption ⁽⁴⁾	
Active (W)	<25
Idle (W)	<5
Endurance/Reliability	
DWPD ⁽⁵⁾	1
UBER	< 1 sector per 10 ¹⁸ bits read
MTBF (million hours)	2.5
Limited Warranty (years)	5
Temperature	
Operating Temp. (°C)	0 - 70
Non-Operating Temp. (°C)	-40 - 85
Physical Dimension	
Length (mm)	118.75
Width (mm)	33.75
Height (mm)	15
Weight (g)	<100
Part Number	
ISE FW	DP20BH0815T3P3116T310
SED FW	DP20BH0815T3P2116T310
Non-SED FW	DP20BH0815T3P0116T310

(1) 1 TB = 10¹² bytes.

(2) Sequential Performance is based on FIO on Linux, 512KB data size, with QD=32, 1 job.

(3) Random Performance is based on FIO on Linux, 4KB data size, QD=128, 8 jobs.

(4) Power consumption (average RMS) is measured during the sequential read/write and random read/write operations performed by iometer with the conditions described in (2) and (3).

(5) The results of DWPD are obtained in compliance with JESD219A standards.



The data within this specification is subject to change by Phison without notice. Performance numbers may vary based on system configuration and testing conditions. Copyright © 2025 Phison Electronics. All rights reserved.



ES France - Mobilité & Systèmes Embarqués
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 80



e-mail : mse@es-france.com
Site Web : www.es-france.com