

## High Power Directional Coupler, 690-2700MHz, 40dB, N-Male or Female Input, 50Ω

**HIGH DIRECTIVITY... 30dB TYPICAL PERFORMANCE!**

**WADC-0727-40-XXX**



The WADC-0727-40-XXX is a high power 40 dB directional coupler covering 690 to 2700 MHz, supporting key cellular, LTE, and wireless infrastructure bands. Designed using an air dielectric coaxial structure, this coupler delivers low insertion loss, high directivity, and excellent power handling for forward and reverse signal monitoring. Typical applications include RF power monitoring, transmitter protection, VSWR measurement, distributed antenna systems (DAS), base station infrastructure, and general-

purpose RF test setups requiring accurate sampling of high-power signals across broadband frequencies. The model is configurable and may be ordered in single or dual configurations. The input connector is offered with a standard N-Female, or an N-Male may be configured to directly connect to an amplifier output, thereby eliminating the needs for cables and adapters, which may add loss and mismatch to the high-power output.

### Electrical

Parameter	Low Band	Mid Band	High Band	Unit
Frequency Range	690-1000	1000-2000	2000-2700	MHz
Impedance	50			Ω
Coupling (Nominal ± Range)	41 +2/-2.5	40 +1/-2	39 +2.5/-3	dB
Coupling (Guaranteed Range)	38.5 - 43.0	38.0 - 41.0	36.0 - 41.5	dB
Mainline Loss <sup>1</sup>	0.15	0.15	0.20	dB, max.
Directivity	25	25	22	dB, min.
Mainline Return Loss	25			dB, min.
Secondary Line Return Loss	20			dB, min.
Isolation	66	65	61	dB, typ.
Forward or Reverse Power, at +25 °C, Sea Level (CW) <sup>2</sup>	500	375	300	W, max.
Forward or Reverse Power, at +85 °C, Sea Level (CW) <sup>2</sup>	400	300	250	W, max.
Termination Power	1			W, max.
DC Current (Input-Output)	5			A, max.



## Mechanical and Environmental



Connector Interface	N Female	RoHS Status <sup>4</sup>	RoHS3 Compliant
Operating Temperature <sup>3</sup>	-55 to +85 °C	REACH Status <sup>4</sup>	REACH Unaffected
Storage Temperature	-55 to +100 °C	Enclosure Material	Aluminum
Nominal Weight	205 g (7.2 oz)	Connectors Material	Brass, Tri-Alloy or Gold Plated
Operating Humidity	10-90% (non-condensing)	Contacts Material	Beryllium Copper, Gold Plated
Operating Environment	Indoor Use Only	Insulators Material	Virgin PTFE
HTSUS Code	8525.50.3035	Finish	Green Paint
ECCN	EAR99		

1. Mainline loss includes coupling loss.
2. All output ports must be terminated in a 50-ohm load with 1.2:1 max VSWR. Ratings assume adequate thermal conduction to mounting surface.
3. Electrical specifications are tested at +25 °C.
4. To the best of our knowledge at the time of publication.



## Explanation of Part Numbers

Product Code	Frequency Range Code	Value (dB)	Configuration Code	Input Connector
WADC	0727	40	1	NF
	0430: 400-3000MHz 0727: 690-2700MHz 1040: 1-4GHz		1: Single 2: Dual	NF: N-Female NM: N-Male

## Functional Schematic





## Outline Drawings



Dimensions are in inches, [mm] shown for convenience. Tolerances on 2-pl decimals:  $\pm 0.03$ . 3-pl decimals:  $\pm 0.015$ .









Dimensions are in inches, [mm] shown for convenience. Tolerances on 2-pl decimals:  $\pm 0.03$ . 3-pl decimals:  $\pm 0.015$ .







## Typical Performance at +25 °C









## Typical Performance Over Temperature





## Repeatability in Production





## Typical Performance Data

Frequency (MHz)	Return Loss (dB)			Mainline Loss (dB)	Coupling (dB)	Directivity (dB)
	In	Out	Cpl.	In-Out	In-Cpl.	
100	41.43	41.27	44.24	0.03	57.24	34.39
200	36.82	38.75	42.15	0.01	51.35	35.44
300	34.18	34.52	41.75	0.04	47.98	35.27
400	34.42	34.03	42.53	0.05	45.68	36.07
500	35.02	34.69	43.92	0.06	43.97	35.65
600	36.91	36.81	46.02	0.06	42.66	35.28
700	41.04	41.32	48.81	0.06	41.65	35.25
800	49.53	52.33	52.07	0.07	40.89	35.25
900	43.35	43.64	53.95	0.07	40.26	35.70
1000	37.75	37.67	54.72	0.07	39.79	35.75
1100	34.90	34.97	56.21	0.08	39.50	35.61
1200	33.67	33.74	60.62	0.08	39.31	36.14
1300	33.59	33.65	56.01	0.08	39.26	36.04
1400	34.62	34.58	49.06	0.09	39.29	35.72
1500	36.95	36.90	44.02	0.09	39.36	35.55
1600	42.01	42.12	40.32	0.09	39.52	34.78
1700	54.53	60.94	37.54	0.09	39.73	34.24
1800	40.97	41.67	35.24	0.09	39.97	33.25
1900	35.34	35.92	33.45	0.09	40.11	32.80
2000	32.29	32.72	31.93	0.10	40.27	31.64
2100	30.50	30.75	30.63	0.10	40.30	31.21
2200	29.45	29.52	29.53	0.10	40.18	30.84
2300	29.06	28.87	28.62	0.10	39.95	31.08
2400	29.13	28.76	27.87	0.10	39.66	31.12
2500	29.71	29.16	27.23	0.11	39.23	31.75
2600	30.80	30.34	26.65	0.11	38.79	32.46
2700	32.72	32.41	26.20	0.11	38.36	33.49
2800	36.35	36.23	25.86	0.11	37.90	34.58
2900	46.33	46.77	25.63	0.11	37.49	35.56
3000	42.04	41.68	25.56	0.12	37.15	36.27

The information contained in this document is accurate to the best of our knowledge and representative of the product described herein at the date of publication. It may be necessary to make modifications to the product and/or documentation of the product. Werbel Microwave LLC reserves the right to make such changes as required without notice. Unless otherwise stated, all specifications and dimensions are nominal. Werbel Microwave LLC does not make any representation or warranty regarding the suitability of the product described herein for any particular purpose or application, and Werbel Microwave LLC does not assume any liability arising out of the use of any part of documentation. This document gives only a description of the product(s) and shall not form part of any contract. Please contact a Werbel Microwave LLC Applications Engineer for the most current specification drawing.

Reliability testing was performed as an internal requalification of the product to substantiate the published specifications, which were previously arrived at by calculation and/or similarity to existing products. The results of these tests are provided as a courtesy and shall not form part of a contract or warranty. While reliability tests may depict the product being tested beyond the published specification ratings for the purpose of stress testing the product, this does not imply that the product should be operating above the rated limits for any length of time. Specifications related to reliability (e.g., performance over temperature, power handling, DC current, HI-POT) are "designed to meet" and are not individually tested in production of commercially available products. Please contact a Werbel Microwave LLC Applications Engineer if specific reliability testing is needed on a particular product.

