

## Cavi elettrici SK

### SK electric cables



Cavo con guaina esterna per immersione permanente secondo Norma NF C15-100-AD8 ideale per pompe sommerse.

Cavo idoneo per immersione in:

- acque reflue;
- miscele di acque e idrocarburi;
- percolato;
- siti contaminati.

Resistente a oli, solventi e idrocarburi diluiti al 10%.

Temperatura di impiego in immersione: max +80 °C in caso di acque reflue, max +50 °C in caso di acque contaminate.

Max profondità di immersione: 120 m.

*Cable with special external sheath for permanent immersion according to NF C15-100-AD8 rule ideal for submersible pumps.*

*Cable suitable for immersion in:*

- domestic waste water;*
- water and hydrocarbons mixture;*
- leachate;*
- contaminated sites.*

*Resistant to oils, solvents, hydrocarbons diluted 10%.*

*Working temperature in immersion: max +80 °C in case of wastewater, max +50 °C in case of contaminated liquids.*

*Maximum immersion depth: 120 m.*

CODICE - Code	DESCRIZIONE - Description	PESO - Weight kg/m
001.07.001.0015	CAVO TONDO SK 4G1,5 per motore monofase <i>SK 4G1,5 round cable for single-phase motor</i>	0,16
001.07.001.0020	CAVO TONDO SK 4G1,5 per motore trifase <i>SK 4G1,5 round cable for three-phase motor</i>	0,16

