



OBB123 12" Optical Bonding

16:6 Native Resolution 1920 x 720

OBB123-RC6000-UD7T00-1.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Power Consumption (Typ)	I / O
700	1000 : 1	85° / 85° / 85° / 85°	AG (Optional)	USB	20W	HDMI / DP

Dimensions(mm)(w) x (H) x (D) 328.5 x 146.5 x 43.7 3 Year Warranty RoHS

Agency Approvals: FCC / CE / UKCA



OTB153 15"

16:3 Native Resolution 1280 x 242

OTB153-RC5000-UD4500-1.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Power Consumption (Typ)	I / O
400	1000 : 1	85° / 85° / 85° / 85°	AG (Optional)	USB	20W	HDMI / DP

Dimensions(mm)(w) x (H) x (D) 413.0 x 110.0 x 46.9 3 Year Warranty RoHS

Agency Approvals: FCC / CE / UKCA



OTB163 16"

16:3 Native Resolution 1366 x 238

OTB163-RC5000-UD4500-1.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Power Consumption (Typ)	I / O
400	1000 : 1	89° / 89° / 89° / 89°	AG (Optional)	USB	20W	HDMI / DP

Dimensions(mm)(w) x (H) x (D) 457.0 x 120.0 x 47.8 3 Year Warranty RoHS



OTB193 19"

16:3 Native Resolution 1920 x 360

OTB193-RC5000-UD4500-1.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Power Consumption (Typ)	I / O
400	3000 : 1	89° / 89° / 89° / 89°	AG (Optional)	USB	22W	HDMI / DP

Dimensions(mm)(w) x (H) x (D) 529.4 x 142.6 x 46.7 3 Year Warranty RoHS

