



Panel Mount Touchmonitor

Touch

PTL15S 15" **IP65** **4:3** Native Resolution 1024 x 768

PTL15S-RC4W00-UH3A00-1.0 Multi-Touch **ZB** **PCAP**

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
350	2500 : 1	88° / 88° / 88° / 88°	AG (Optional)	USB	3.8	18W	VGA / HDMI

Dimensions(mm)(w) x (H) x (D) 378.3 x 302.3 x 54.2 **3** Year Warranty **RoHS** Operating Temperature Range: -20~60°C
Agency Approvals: CCC / CE / FCC / UKCA



PTL15S 15" **IP65** **4:3** Native Resolution 1024 x 768

PTL15S-RC4W00-UD3A00-1.0 Multi-Touch **ZB** **PCAP**

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
350	2500 : 1	88° / 88° / 88° / 88°	AG (Optional)	USB	3.8	18W	VGA / DVI / HDMI / DP

Dimensions(mm)(w) x (H) x (D) 378.3 x 302.3 x 54.2 **3** Year Warranty **RoHS** Operating Temperature Range: -20~60°C
Agency Approvals: CCC / CE / FCC / UKCA



PTL103 10" **IP65** **16:10** Native Resolution 1280 x 800

PTL103-RC4W00-UH4A00-1.0 Multi-Touch **ZB** **PCAP**

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
400	900 : 1	85° / 85° / 85° / 85°	AG (Optional)	USB	2.2	7W	VGA / HDMI

Dimensions(mm)(w) x (H) x (D) 286.2 x 204.8 x 54.2 **3** Year Warranty **RoHS** Operating Temperature Range: -20~60°C
Agency Approvals: CCC / CE / FCC / UKCA



PTL103 10" **IP65** **16:10** Native Resolution 1280 x 800

PTL103-RC4W00-UP4A00-1.0 Multi-Touch **ZB** **PCAP**

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
400	900 : 1	85° / 85° / 85° / 85°	AG (Optional)	USB	2.2	7W	VGA / DP

Dimensions(mm)(w) x (H) x (D) 286.2 x 204.8 x 54.2 **3** Year Warranty **RoHS** Operating Temperature Range: -20~60°C
Agency Approvals: CCC / CE / FCC / UKCA



PTL153 15.6" **IP65** **16:9** Native Resolution 1920 x 1080

PTL153-RC4W00-UD3F00-1.0 Multi-Touch **ZB** **PCAP**

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
350	800 : 1	89° / 89° / 89° / 89°	AG (Optional)	USB	3.35	15W	VGA / DVI / HDMI / DP

Dimensions(mm)(w) x (H) x (D) 412.9 x 262.2 x 54.2 **3** Year Warranty **RoHS** Operating Temperature Range: -20~60°C
Agency Approvals: CCC / CE / FCC / UKCA



PTL153 15.6" **IP65** **16:9** Native Resolution 1920 x 1080

PTL153-RC4W00-UH4200-2.0 Multi-Touch **ZB** **PCAP**

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
400	800 : 1	85° / 85° / 85° / 85°	AG (Optional)	USB	3.34	20W	VGA / HDMI

Dimensions(mm)(w) x (H) x (D) 412.9 x 262.2 x 56.7 **3** Year Warranty **RoHS** Operating Temperature Range: -20~40°C
Agency Approvals: CCC / CE / FCC / UKCA



PTL223 21.5" **IP65** **16:9** Native Resolution 1920 x 1080

PTL223-RC5W00-UD3F00-1.0 Multi-Touch **ZB** **PCAP**

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
350	1000 : 1	89° / 89° / 89° / 89°	AG (Optional)	USB	6.3	27W	VGA / DVI / HDMI / DP

Dimensions(mm)(w) x (H) x (D) 559.7 x 353.8 x 55.7 **3** Year Warranty **RoHS** Operating Temperature Range: -20~60°C
Agency Approvals: CCC / CE / FCC / UKCA



PTL223 21.5" **IP65** **16:9** Native Resolution 1920 x 1080

PTL223-RC5W00-UH2200-2.0 Multi-Touch **ZB** **PCAP**

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
250	3000 : 1	89° / 89° / 89° / 89°	AG (Optional)	USB	6.29	20W	VGA / HDMI

Dimensions(mm)(w) x (H) x (D) 559.7 x 353.8 x 55.7 **3** Year Warranty **RoHS** Operating Temperature Range: -20~40°C
Agency Approvals: CCC / CE / FCC / UKCA

