



OTL15F 15"

4:3 Native Resolution
1024 × 768

OTL15F-RS3000-CC3A00-1.1

SAW

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
350	2500 : 1	88° / 88° / 88° / 88°	AG (Optional)	USB & RS232	4.5	25W	VGA / DVI

Dimensions(mm)(w) × (H) × (D) 353.0 × 277.0 × 37.8

3 Year Warranty RoHS

Agency Approvals: CCC / FCC / CE / UKCA



OTL17F 17"

5:4 Native Resolution
1280 × 1024

OTL17F-RS3000-CC2A00-1.1

SAW

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
250	1000 : 1	85° / 85° / 80° / 80°	AG (Optional)	USB & RS232	6	25W	VGA / DVI

Dimensions(mm)(w) × (H) × (D) 388.0 × 320.5 × 37.6

3 Year Warranty RoHS

Agency Approvals: CCC / FCC / CE / UKCA



OTL19F 19"

5:4 Native Resolution
1280 × 1024

OTL19F-RS3000-CC2A00-1.1

SAW

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
250	1000 : 1	85° / 85° / 80° / 80°	AG (Optional)	USB & RS232	6	25W	VGA / DVI

Dimensions(mm)(w) × (H) × (D) 430.0 × 353.0 × 37.6

3 Year Warranty RoHS

Agency Approvals: CCC / FCC / CE / UKCA



OTL15F 15"

4:3 Native Resolution
1024 × 768

OTL15F-RC3000-UH3A00-1.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
350	2500 : 1	88° / 88° / 88° / 88°	AG (Optional)	USB	4.8	15W	VGA / HDMI

Dimensions(mm)(w) × (H) × (D) 354.7 × 278.7 × 46.0

3 Year Warranty RoHS

Agency Approvals: CCC / FCC / CE / UKCA



OTL17F 17"

5:4 Native Resolution
1280 × 1024

OTL17F-RC5000-UH2A00-2.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
250	1000 : 1	85° / 85° / 80° / 80°	AG (Optional)	USB	5.2	20W	VGA / HDMI

Dimensions(mm)(w) × (H) × (D) 393.3 × 327.4 × 39.8

3 Year Warranty RoHS

Agency Approvals: CCC / FCC / CE / UKCA



OTL19F 19"

5:4 Native Resolution
1280 × 1024

OTL19F-RC5000-UH2A00-2.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
250	1000 : 1	85° / 85° / 80° / 80°	AG (Optional)	USB	5.5	20W	VGA / HDMI

Dimensions(mm)(w) × (H) × (D) 433.6 × 356.6 × 39.8

3 Year Warranty RoHS

Agency Approvals: CCC / FCC / CE / UKCA



OTL105 10"

16:10 Native Resolution
1280 × 800

OTL105-RC3000-UC4A00-1.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
400	900 : 1	85° / 85° / 85° / 85°	AG (Optional)	USB	3.8	15W	VGA / DVI

Dimensions(mm)(w) × (H) × (D) 261.3 × 179.3 × 42.8

3 Year Warranty RoHS

Agency Approvals: CCC / FCC / CE / UKCA



OTL155 15.6"

16:9 Native Resolution
1920 × 1080

OTL155-RC3C00-UH4200-1.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
400	1200 : 1	85° / 85° / 85° / 85°	AG (Optional)	USB	4.8	18W	VGA / HDMI

Dimensions(mm)(w) × (H) × (D) 388.6 × 238.6 × 40.8

3 Year Warranty RoHS

Agency Approvals: CCC / FCC / CE



OBL155 15.6" Optical Bonding

16:9 Native Resolution
1920 × 1080

OBL155-RC30A0-UT3F0S-2.0 No Stand

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
350	1000 : 1	85° / 85° / 85° / 85°	AG (Optional)	USB	3.2	9.8W	USB-C

Dimensions(mm)(w) × (H) × (D) 395.4 × 245.4 × 27.6

3 Year Warranty RoHS

Agency Approvals: FCC / CE / UKCA



OTL225 21.5"

16:9 Native Resolution
1920 × 1080

OTL225-RC5A00-UH2200-1.0 No Stand

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
250	3000 : 1	89° / 89° / 89° / 89°	AG (Optional)	USB	5.8	20W	VGA / HDMI

Dimensions(mm)(w) × (H) × (D) 529.0 × 325.6 × 39.8

3 Year Warranty RoHS

Agency Approvals: CCC / FCC / CE / UKCA



OTL22W 21.5"

16:9 Native Resolution
1920 × 1080

OTL22W-RC3A00-UH2200-1.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
250	3000 : 1	89° / 89° / 89° / 89°	AG (Optional)	USB	5.1	20W	VGA / HDMI

Dimensions(mm)(w) × (H) × (D) 529.5 × 316.5 × 40.0

3 Year Warranty RoHS

Agency Approvals: CCC / FCC / CE / UKCA



OBL228 21.5"

16:9 Native Resolution
1920 × 1080

OBL228-RC30A0-UH2F0S-1.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
250	1000 : 1	89° / 89° / 89° / 89°	AG (Optional)	USB	4.56	20W	HDMI

Dimensions(mm)(w) × (H) × (D) 505.2 × 296.8 × 36.8

3 Year Warranty RoHS

Agency Approvals: CCC / FCC / CE / UKCA



OTL245 23.8"

16:9 Native Resolution
1920 × 1080

OTL245-RC5000-UH4200-2.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
400	3000 : 1	89° / 89° / 89° / 89°	AG (Optional)	USB	6.3	22W	VGA / HDMI

Dimensions(mm)(w) × (H) × (D) 575.8 × 352.9 × 48.8

3 Year Warranty RoHS

Agency Approvals: CCC / FCC / CE / UKCA



OTL275 27"

16:9 Native Resolution
1920 × 1080

OTL275-RC5000-UH3F00-2.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
300	3000 : 1	89° / 89° / 89° / 89°	AG (Optional)	USB	11.2	40W	VGA / HDMI

Dimensions(mm)(w) × (H) × (D) 645.6 × 387.7 × 48.8

3 Year Warranty RoHS

Agency Approvals: CCC / FCC / CE / UKCA



OTL279 27"

Slim Border

16:9 Native Resolution
1920 × 1080

OTL279-RC4000-UD3F00-1.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
300	1000 : 1	89° / 89° / 89° / 89°	AG (Optional)	USB	6.35	40W	HDMI / DP

Dimensions(mm)(w) × (H) × (D) 614.9 × 362.4 × 57.0

3 Year Warranty RoHS

Agency Approvals: CCC / FCC / CE / UKCA



OTL439 43"

4K Slim Border

16:9 Native Resolution
3840 × 2160

OTL439-RC4000-UD5U00-1.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
500	1200 : 1	89° / 89° / 89° / 89°	AG (Optional)	USB	22.5	95W	HDMI / HDMI / DP

Dimensions(mm)(w) × (H) × (D) 969.9 × 558.3 × 66.3

3 Year Warranty RoHS

Agency Approvals: FCC / CE / UKCA



OTL555 55"

4K

16:9 Native Resolution
3840 × 2160

OTL555-RC5000-UD6U00-2.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
600	1200 : 1	89° / 89° / 89° / 89°	AG (Optional)	USB	35.2	186W	DVI / HDMI / DP

Dimensions(mm)(w) × (H) × (D) 1059.4 × 736.4 × 71.3

3 Year Warranty RoHS

Agency Approvals: FCC / CE / UKCA

