

# DuraBrite Series Outdoor High Bright Monitors

Touch

**PSL10S** 10" Sunlight Readable Light sensor 4:3 Native Resolution 1024 x 768

**PSL10S-RC80A0-UHAAL0-1.0** Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
1300	1000 : 1	88° / 88° / 88° / 88°	AG (Optional)	USB	2.46	17W	VGA / HDMI

Dimensions(mm)(w) x (H) x (D) 278.6 x 233.6 x 61.1 1 Year Warranty RoHS

Agency Approvals: CE / FCC / UKCA / CCC



**PSL073** 7" Sunlight Readable Light sensor 15:9 Native Resolution 800 x 480

**PSL073-RC80A0-UHBAL0-1.0** Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
1500	1000 : 1	88° / 88° / 88° / 88°	AG (Optional)	USB	1.47	9W	VGA / HDMI

Dimensions(mm)(w) x (H) x (D) 213.8 x 156.7 x 61.1 1 Year Warranty RoHS

Agency Approvals: CE / FCC / UKCA



**OSL223** 21.5" Sunlight Readable Light sensor 16:9 Native Resolution 1920 x 1080

**OSL223-RC80A0-UDA2L0-3.0** Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
1500	400 : 1	89° / 89° / 89° / 89°	AG (Optional)	USB	8.1	98W	VGA / DVI HDMI / DP

Dimensions(mm)(w) x (H) x (D) 536.0 x 322.7 x 73.4 1 Year Warranty RoHS

Agency Approvals: CE / FCC / UKCA



**RSL276** 27" Sunlight Readable Light sensor 16:9 Native Resolution 1920 x 1080

**RSL276-RC80A0-UDB2L0-1.0** Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
1500	1000 : 1	89° / 89° / 89° / 89°	AG (Optional)	USB	12.1	110W	VGA / DVI HDMI / DP

Dimensions(mm)(w) x (H) x (D) 658.0 x 414.9 x 72.0 1 Year Warranty RoHS

Agency Approvals: CE / FCC / UKCA



High Bright 39