



## OTL15M 15.6"

16:9 Native Resolution 1920 x 1080

### OTL15M-LC40A0-UH420S-1.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
400	1200 : 1	85° / 85° / 85° / 85°	AG	USB	3.2	20W	VGA / HDMI

Dimensions(mm)(w) x (H) x (D) 388.6 x 238.6 x 40.8 3 Year Warranty RoHS

Agency Approvals: EN 60601-1-2 / IEC 60601-1-2 / FCC / CE / UL



## OTL22M 21.5"

16:9 Native Resolution 1920 x 1080

### OTL22M-LC50A0-UH220S-1.0

Multi-Touch ZB PCAP

Luminance (nits)	Contrast Ratio	Viewing Angle (L/R/U/D)	Surface Treatment	Touch Interface	Weight (Kg)	Power Consumption (Typ)	I / O
250	3000 : 1	89° / 89° / 89° / 89°	AG	USB	5.95	20W	VGA / HDMI

Dimensions(mm)(w) x (H) x (D) 529.0 x 325.6 x 42.8 3 Year Warranty RoHS

Agency Approvals: EN 60601-1-2 / IEC 60601-1-2 / FCC / CE / UL



Medical Grade 40