

AP-LDLD1548-01

Industrial Computing Platform Partner

Industrial Monitor 15" 1600 nits, TFT, AC adaptor, VGA, AV, Housing



Features

- Wide Viewing Angle
- Fast Response Time
- High Contrast Ratio
- Very High Brightness
- Sunlight Readable

Specifications

System	
Form Factor	Industrial Monitor
OS Support	MS DOS, Windows® 2000, Windows® XP
Display	
Size	15"
Resolutions	1024 x 768
Type	TFT
Max. Colors	262K
Dot Size	0.297 x 0.297
Luminance	1600 nit
Contrast Ratio	400:1
Viewing Angle	140°/120°(Typ.)
Back Light MTBF	50000
Brightness Control	Yes
LCD Interface	LVDS
VGA input	Yes
Video input	Yes
S-video input	Yes
I/O	
Vedio	1 x S-video in/ 1 x Video-in
Mechanical and Environmental	
Power Requirement	115/230 V AC
Operating Temperature	0~50°C
Operating Humidity	90%
Storage Humidity	95%
Vibration	1.5G, 10Hz ~ 200Hz ~ 10Hz 30 minutes for each Axis (X, Y, Z)
Shock	50G/20ms, ±X, ±Y, ±Z Half-sin, one time
EMC	150 pF, 150Ω, 10kV, 1 second, 9 position on the panel, 10 times each place
Dimension	389(w) x 325(H) x 60.5(D)
Construction	Heavy-duty steel chassis

Mounting	VESA 75
Front Panel Color	Black
Net Weight	3.92kg

Ordering Information

• AP-LDLD1548-01

Industrial Monitor 15" 1600 nits, TFT, AC adaptor, VGA, AV, Housing.