



Agilent
E3620A and E3630A
Non-Programmable DC Power Supplies

Data Sheet



Anticipate — Accelerate — Achieve



Agilent Technologies

Reliable power, repeatable results

- Linear power supply
- Dual or triple output
- 10-turn voltage and current control
- Low noise and excellent regulation



Affordable, full-featured benchtop power supplies provide excellent performance and flexibility

Multiple-output non-programmable models

The E3620A and E3630A low-cost benchtop power supplies give you the performance of system power supplies at a decent price. Both supplies provide clean power with excellent regulation and a fast transient response.

With multiple supplies in a compact unit, the E3620A and E3630A provide excellent performance while saving space on your bench. Both instruments feature a tight 0.01 percent line and load regulation and a low normal mode noise specification of less than 0.35 mV to ensure clean power for precision circuitry. With a common mode current specification of less than 1 μ A, both multiple-output power supplies minimize the power line current injection.

The E3620A and E3630A feature separate digital panel meters so you can monitor the voltage and current simultaneously. They also protect your DUT against overload and short-circuit damage.

Smooth turn-on and turn-off transitions keep power spikes out of your circuits. Auto-tracking permits equal or proportional voltage sharing, and allows control of output voltage from one master unit. The master and slave supplies have the same output polarity with respect to a common bus or ground. This operation is useful where simultaneous turn-up, turn-down or proportional control of all power supplies is required.

E3620A dual-output power supply

The 50-watt E3620A dual-output power supply provides two 0 V to 25 Vdc outputs with the maximum current of 1 A to satisfy most bench requirements. The outputs are completely independent and isolated.

E3630A triple-output power supply with auto-tracking feature

The 35-watt E3630A triple-output power supply provides three DC outputs: 0 to 6 V with a maximum current of 1 to 2.5 A and 0 to 20 V and 0 to -20 V with a maximum current of 0.5 A. An auto-tracking feature lets you use one voltage control to adjust the +20 V and -20 V outputs simultaneously. The outputs track each other to within 1 percent, making it easy to adjust the power supply for circuits requiring balanced voltages.

Specifications

	E3620A	E3630A
Features	Isolated dual outputs, 10 turn pots CV, CL	Tracking, CV, CL (±20 V) CV, CF (+6 V)
Number of outputs	2	3
Number of Output Ranges	1	1
DC Output Rating	25 V, 1 A 25 V, 1 A	+6 V, 2.5 A +20 V, 0.5 A −20 V, 0.5 A
Load and Line Regulation	< 0.01% + 2 mV	
Ripple and Noise (20 Hz to 20 MHz)		
Normal mode voltage	< 350 μVrms, < 1.5 mVpp	
Normal mode current	–	
Common mode current	< 1 μArms	
Transient Response Time	< 50 μsec following a change in output current from full load to half load for output to recover within:	
	15 mV	
Meter Accuracy	±0.5% + 2 counts at 25 °C ±5 °C	
Meter Resolution		
Voltage	10 mV (0–20 V), 100 mV (>20 V)	10 mV
Current	1 mA	10 mA
Isolation	240 Vdc	

Supplemental characteristics

	E3620A	E3630A
Control Mode	CV/CL	CV/CL (±20 V) CV/CF (+6 V)
Temperature Coefficient per °C		
Voltage	< 0.02% + 1 mV	
Current	—	
Output Drift		
Voltage	Less than 0.1% + 5 mV total drift for 8 hours after initial warm-up of 30 minutes	
Current	N/A	
Temperature Range		
	Derate output current 50% between 40 °C to 55 °C	
Cooling	Convection cooling	
Isolation	±240 Vdc	
AC Input	100 Vac ±10%, 47–63 Hz (opt. 0E9) 115 Vac ±10%, 47–63 Hz (std) 230 Vac ±10%, 47–63 Hz (0E3)	
Weight	5.0 kg (11.0 lbs) net, 6.25 kg (13.8 lbs) shipping	3.8 kg (8.4 lbs) net, 5.1 kg (11.3 lbs) shipping
Size	88.1 mm H x 212.3 mm W x 392.4 mm D 3.5" H x 8.4" W x 15.4" D	88.1 mm H x 212.3 mm W x 318.4 mm D 3.5" H x 8.4" W x 12.5" D
Warranty	Three year for E3600 Series power supplies Three months for standard shipped accessories	
Product Regulation	Certified to CSA 22.2 No. 231; conforms to IEC 1010-1; carries CE mark; complies with CISPR-11, Group 1, Class A, KC South Korean EMC Mark, Canadian ICES/NMB-001, Australian C Tick Mark	

Ordering information

E3620A Dual-output Power Supply
E3630A Triple-output Power Supply

Standard shipped accessories

Product Reference CD, power cord

Power options

Opt. 0E3 230 Vac $\pm 10\%$
Opt. 0EM 115 Vac $\pm 10\%$
Opt. 0E9 100 Vac $\pm 10\%$

Other options

Opt. 1CM or 34190A rackmount kit*
(Only applicable for E3620A)
Opt. UK6 Commercial calibration
certificate with test result data
E3600A-100 Test lead kit

Manual sets

Please visit
www.agilent.com/find/manuals
for the latest revisions of manuals.

Rackmount kits*

E3620A

To rackmount two instruments
side-by-side

- Lock-link Kit (P/N 5061-9694)
- Flange Kit (P/N 5063-9212)
or 34191A

To rackmount one or two instruments in
a sliding support shelf

- Support Shelf (P/N 5063-9255)
- Slide Kit (P/N 1494-0015)
required for support shelf

For a single instrument, also order filler
panel (P/N 5002-3999)

* Rackmounting with 1CM or lock-link/
flange kit requires

- Agilent or customer support rails
- Agilent Support Rails-E3663AC.



myAgilent

www.agilent.com/find/myagilent

A personalized view into the information most relevant to you.



Three-Year Warranty

www.agilent.com/find/ThreeYearWarranty

Beyond product specification, changing the ownership experience. Agilent is the only test and measurement company that offers three-year warranty on all instruments, worldwide.

Agilent Channel Partners

www.agilent.com/find/channelpartners

Get the best of both worlds: Agilent's measurement expertise and product breadth, combined with channel partner convenience.

www.agilent.com
www.agilent.com/find/trustedpower

For more information on Agilent Technologies' products, applications or services, please contact your local Agilent office. The complete list is available at:
www.agilent.com/find/contactus

Americas

Canada	(877) 894 4414
Brazil	(11) 4197 3600
Mexico	01800 5064 800
United States	(800) 829 4444

Asia Pacific

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 112 929
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Other AP Countries	(65) 375 8100

Europe & Middle East

Belgium	32 (0) 2 404 93 40
Denmark	45 45 80 12 15
Finland	358 (0) 10 855 2100
France	0825 010 700*
	*0.125 €/minute
Germany	49 (0) 7031 464 6333
Ireland	1890 924 204
Israel	972-3-9288-504/544
Italy	39 02 92 60 8484
Netherlands	31 (0) 20 547 2111
Spain	34 (91) 631 3300
Sweden	0200-88 22 55
United Kingdom	44 (0) 118 927 6201

For other unlisted countries:

www.agilent.com/find/contactus

(BP-11-07-13)

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 2009–2014
Published in USA, January 8, 2014
5968-9727EN



Agilent Technologies