

# Open Frame LCD

## Open Frame LCD

**19"(16:9)**

### Specifications

**RoHS**  
COMPLIANT  
2002/95/EC

|                                |                              |
|--------------------------------|------------------------------|
| Model Name                     | W19L300-OFM1                 |
| Viewable Size Image            | 19"(16:9)                    |
| Active Display Area(mm)        | 410.4(H)x256.5(V)            |
| Pixel Pitch(mm)                | 0.285X0.285                  |
| Number of Pixels               | 1440x900                     |
| Contrast Ratio                 | 850:1(typ.)                  |
| Display Color                  | 16.2M(6bit/FRC)              |
| Brightness(cd/m <sup>2</sup> ) | 300(typ.)                    |
| Viewing Angle(CR>=10)          | -85~85(H);-80~80(V)          |
| Synchronization Range          |                              |
| Horizontal/Vertical            | 31.5~60.0KHz/60~75Hz         |
| Recommended Resolution         | 1440x900@ 60Hz               |
| Signal Connector               | 15 pin D-Sub                 |
| Power Source                   | AC100~240V, Universal, ±10%  |
| Power Consumption              | 35W typical,normal operation |
| Power Management               | VESA DPMS Compliant          |
| Plug & Play                    | VESA DDC 1/2B                |
| Optional Video Input           | S-Video/ Composite           |
| Optional DVI Input             | Yes                          |
| Optional Touch Screen          | No                           |

Remarks:W19L300 series= VGA input only

W19L340 series= VGA+Video Input



### Mechanical Drawing

