

The serial of GT glossmeters are designed and manufactured according to international standard ISO2813,ASTMD523,DIN67530 and China standard GB9754,GB9966,GB/T3891. The technical parameters up to JJG696-2002.



Applications:

1. Measurement of Paint and Dope surface gloss on Car, Electronic appliance and Musical instrument industry.
2. Measurement of floor board, marble, granite and ceramic tile gloss on architecture, decoration industry.
3. Measurement of printing ink and paper on Printing and Casing industry.
4. Measurement of the others need to be measured.
5. Hard drawn aluminum alloys

Features:

1. Small and light, real easy to be carried and used.
2. One 1.5 mignon alkaline Battery can be used for almost 60 hours and 10000 reading.
3. High stability
4. Long-term stable light source needs no replacing for ever.
5. Quartz crystal standard board, no excursion.

Spec.	GTS	GT60	GT60 Plus
Measuring range	0~199.9Gs	0~199.9Gs	L:0-199.9Gs H:0-1999Gs
Readout error	± 1.5Gs	± 1.0Gs	L:±1.2Gs H:±12Gs
Stability	0.4Gs	0.4Gs	0.4Gs
Aperture	20°60°φ10mm 85° φ7mm	φ13mm	φ13mm
Dimension	140×32×64mm	114×32×64mm	114×32×64mm
Weight	420g	300g	300g