

Specification

| | |
|----------------------------|--|
| Model | NP-345 |
| Print Method | line thermal |
| Paper Width / Print Width | paper width adjustable 60.0mm/65.0mm/80.0mm, print width 72mm (max.) |
| Print Speed | 70mm/sec |
| Resolution | 8 dots/mm |
| Character Size (dot x dot) | Font A (12 x 24)= 1.5 x 3.00 mm, Font B (7 x19) = 1.13 x 2.13mm |
| Character Types | ASCII, Block graphics, International |
| Barcode | UPC-A, UPC-E, JAN-13 (EAN-8), CODE39, ITF, CODABAR, CODE128, QR code |
| Line Feed Pitch | 0.125 mm |
| Interface | Serial (RS232C), USB (V1.1) |
| Input Buffer | Approx. 10K bytes |
| Operating Voltage | DC24V \pm 5% |
| External Dimensions | 113(W) x 297(D) x 67.5(H) mm |
| Weight | Approx. 1740g |

Paper, Test Data

| | |
|---------------------------------|---|
| Paper Type | Thermal Paper |
| Operating Temperature | 0-45 |
| Storage Temperature | -20 ~ 60 |
| Reliability (Head) | 50Km, More than 100 million pulses |
| (Auto Cutter) | N/A |
| Safety Regulation, EMC Standard | CE mark, EMC, EN550022, Low voltage: EN60950 |
| Attachment | |
| Options | Paper tray guide (1000 sheets holder), AC adaptor |