

Brand New Anemometers



KANOMAX
The Ultimate Measurements



New Climomaster™

2% Accuracy of Air Velocity

Choice of Probes



**New Anemomaster™
Professional & Standard**



New Anemomaster™ LITE



Specifications

New Climomaster™

Air Velocity Range	20 to 9840 fpm (0.01 to 50.0 m/s) *Varies by probe
Accuracy	+/- 2% of reading
Temperature Range	-4 to 158°F (-20 to 70°C)
Accuracy	+/- 1.0°F (0.5°C)
Relative Humidity Range	2.0 to 98.0%RH *Varies by probe
Accuracy	+/- 2.0%RH from 2 to 80%RH, +/- 3.0%RH from 81 to 98%RH
Differential Pressure Range	+/- 5.00 kPa *Option
Accuracy	+/- 3% of reading
Datalogging	Up to 20000 measurements
Interface	USB / (RS232C: only for printer)
Dimensions	W3.4 x H7.4 x D1.6 inches (88 x 188 x 41mm)
Weight	0.9 lbs (400g)



New Climomaster™ Probes

Model	A531-01	A541-01	A561-01	A542-01	A533-01	A543-01
Probe Type	Uni-Directional	Uni-Directional	Uni-Directional	Omni-Directional	Omni-Directional	Omni-Directional
Air Velocity	20 to 6000 fpm	20 to 6000 fpm	20 to 9840 fpm	20 to 6000 fpm	10 to 1000 fpm	10 to 1000 fpm
Temperature	-4 to 158°F	-4 to 158°F	-4 to 158°F	-4 to 158°F	-4 to 158°F	-4 to 158°F
Relative Humidity	2.0 to 98.0%RH	n/a	n/a	n/a	2.0 to 98.0%RH	n/a

New Anemomaster™ Professional & Standard

Model	Professional	Standard
Air Velocity Range	20 to 6000 fpm (0.01 to 30.0 m/s)	
Accuracy	+/- 3% of reading	
Temperature Range	-4 to 158°F (-20 to 70°C)	
Accuracy	+/- 1.0°F (0.5°C)	
Differential Pressure Range	+/- 5.00 kPa *Option	
Accuracy	+/- 3% of reading	
Datalogging	Up to 1500 measurements	No
Interface	USB / (RS232C: only for printer)	No
Dimensions	W3.4 x H7.4 x D1.6 inches, Probe: 79 inch (Telescopic)	
Weight	0.9 lbs (400g)	



New Anemomaster™ LITE

Air Velocity Range	20 to 3940 fpm (0.01 to 20.0 m/s)
Accuracy	+/- 5% of reading
Temperature Range	-4 to 158°F (-20 to 70°C)
Accuracy	+/- 2°F (1°C)
Dimensions	W3.4 x H7.4 x D1.6 inches (60 x 120 x 34mm)
Weight	0.4 lbs (180g)



All specifications subject to change without prior notice

