



Be Ready for Winter

Features

- OLED display with 2000:1 contrast ratio and 160 degrees viewing angle^{3,4}
- 30,000-count resolution
- Measure up to 1000 V AC and DC
- Measure up to 10 A (20 A for 30 s)
- Resistance, diode test, temperature, capacitance
- Low Impedance mode^{2,3,4} and Low Pass Filter
- Peak detection of up to 250 µs
- Continuity test with beeper and backlight^{1,2}
- Seven readings/s measurement rate for voltage and current
- Smooth function for accurately stable readings
- Up to 10,000 points internal memory for data logging
- Bluetooth wireless connectivity with optional U1177A Bluetooth
- PC connectivity with optional U1173A IR-USB cable
- IP 54 certified water and dust resistant
- CAT III 1000 V, CAT IV 600 V safety rating
- Up to 3000m operating altitude
- -40 to 55 °C operating temperature⁴
- 1. U1271A
- 2. U1272A
- 3. U1273A
- 4. U1273AX

Operational down to -40 °C temperature

The U1273AX OLED handheld digital multimeter, the latest addition to U1270 Series, is capable of operating in winter weather down to -40°C temperature. Even in frigid conditions, the U1273AX enables you to achieve immediate and accurate results without the need to warm up in advance.



OLED for more display clarity

Designed with OLED display, you can experience crystal-clear measurement readings with its outstanding 2000:1 contrast ratio. The display also allows wider viewing angles up to 160 degrees ensuring you get the right readings at the first glance even in poorly lit environments.

Increase productivity with *Bluetooth®* wireless connectivity

For wireless connectivity to smartphones and tablets, the U1270 Series is compatible with the U1177A infrared-to-*Bluetooth* adapter for maximum efficiency and productivity in completing measurements tasks. Adding the optional U1177A to a U1270 Series you can easily perform remote monitoring and data logging via Android devices or Windows-based PC.



Key Functions

Water and dust resistance (IP54)

The series' tightly sealed design helps protect against water, dust and damage. Each handheld DMM is certified with IP 54 ratings so that you can carry out tests and measurements with confidence, even in harsh working conditions.

Operational up to 3000 meters altitude

For high altitude applications such as wind farm maintenance, you can measure with confidence using the U1270 Series, capable of measuring up to 3000 meters above sea level.

High measurement rate at seven readings per second for Voltage and Current

You can detect even the slightest change in your sensitive signals (Voltage and Current) with its high measurement rate capability. By clicking the resettable smooth function button, you may customize the readings' sensitivity suitable for various tests.

Visual alert for continuity test (for U1271A and U1272A only)

Continuity detection in noisy and dark environments is made easy with U1270 Series' loud beeper and flashing backlight that indicates continuity and thus improves safety.

Up to 10,000 recording points for manual, auto and event logging

Record measurements on-the-go and transfer data to PC conveniently with the huge internal memory of up to 10,000 recording points. The GUI Data Logging software and optional U1173A IR-USB cable are required to transfer data or perform real time data logging on a PC.

Built-in Low Pass Filter

The U1270 Series offers a 1 kHz LPF or Low Pass Filter to provide accurate Variable Frequency Drive (VFD) output measurements. This function eliminates high frequency noise and harmonics, ensuring motor filter efficiency.



Figure 1. Comparison of voltage output from industrial motor VFD without and with Low Pass Filter functionality.

Key Functions

Low impedance mode

Stray voltages are usually found in non-energized electrical wiring adjacent to powered wires due to capacitive or inductive coupling between these wires. The low impedance mode serves to eliminate false readings by dissipating these stray voltages thus improves safety and measurement efficiency during voltage measurement.

Peak detect at 250 µs

The peak detect function allows you to capture the engine or motor startup transient as fast as 250 µs.



Figure 2. U1272A helps you identify the presence of stray voltage on a disconnected wire running parallel with the wire powering up the VFD to an industrial motor. The image on the right shows the U1272A in low impedance mode.

Front and Back Panel Description



Front panel



Once connected to any HH DMM via Bluetooth adapter you are able to log and view measurements graphically from smart phones and tablets.

1. U1272A, U1273A and U1273AX only

Front and Back Panel Description



Back panel

Choose Among These Four Models

	U1271A	U1272A	U1273A	U1273AX
Basic Features				
Display resolution	30,000 counts	30,000 counts	30,000 counts	30,000 counts
Display	LCD	LCD	OLED	OLED
Backlight	Yes	Yes	N/A	N/A
True RMS	AC	AC + DC	AC + DC	AC + DC
Measurements				
Voltage	Up to 1000 V AC, DC			
Basic dcV accuracy	0.05% + 2 counts			
Current	Up to 10 A (20 A for 30 s)	Up to 10 A (20 A for 30 s)	Up to 10 A (20 A for 30 s)	Up to 10 A (20 A for 30 s)
Resistance	Up to 100 $M\Omega$	Up to 300 $M\Omega$	Up to 300 $M\Omega$	Up to 300 MΩ
Other measurements	Frequency, capacitance, temperature, continuity, diode test			
AC bandwidth	20 kHz	100 kHz	100 kHz	100 kHz
Low pass filter	Yes	Yes	Yes	Yes
Low impedance mode		Yes	Yes	Yes
Smart Ohm	_	Yes	Yes	Yes
Safety and Regulatory				
Over-voltage safety protection	CAT III 1000 V, CAT IV 600 V			
General				
Logging memory	200 points	10,000 points	10,000 points	10,000 points
Connectivity	Optional IR-USB and Bluetooth	Optional IR-USB and Bluetooth	Optional IR-USB and Bluetooth	Optional IR-USB and Bluetooth
Operating temperature	–20 to 55 °C	–20 to 55 °C	–20 to 55 °C	-40 to 55 °C
Altitude	3000 meters	3000 meters	3000 meters	3000 meters
Water and dust ingress protection	IP 54	IP 54	IP 54	IP 54
Battery life	Up to 300 hours 4X AAA Alkaline	Up to 300 hours 4X AAA Alkaline	Up to 60 hours 4X AAA Alkaline	Up to 100 hours 4X AAA Lithium
Warranty	3 years	3 years	3 years	3 years

General Specifications

33,000 counts) - U1273A/U1273AX: Organic LED (QLED) display (with maximum reading of 33,000 counts) Power consumption - U1271A/U1272A: 460 mVA maximum (with backlight enabled) - 4 × 1.5 V Alkaline battery (ANSI/NEDA 240 or IEC IR03), or - 4 × 1.5 V Linic Choride battery (ANSI/NEDA 240 or IEC R03) - 4 × 1.5 V Linic Choride battery (ANSI/NEDA 240 or IEC R03) - 4 × 1.5 V Linic Choride battery (ANSI/NEDA 240 or IEC R03) - 4 × 1.5 V Linic Choride battery (ANSI/NEDA 240 or IEC R03) - 4 × 1.5 V Linic Choride battery (ANSI/NEDA 240 or IEC R03) - Based on new Alkaline batteries for DC voltage measurement: - 0.1273A/U1273AX: - Based on new Alkaline batteries for DC voltage measurement: - 0.1273A/U1273AX: Eased on new Alkaline battery (ange measurement: - 0.1273A/U1273AX:	Display	– U1271A and U1272A: Liquid crystal display (LCD) (with maximum reading of
- U1273A/: Organic LED (0LED) display (with maximum reading of 33,000 counts) Power consumption - U1271A/U1272A: 460 mVA maximum (with maximum bightness) Battery type - 4 × 1.5 V Alkaline battery (ANSI/NEDA 24A or IEC L803), or 4 × 1.5 V Zinc Chloride battery (ANSI/NEDA 24H or IEC R03) Battery life - 4 × 1.5 V Lithium battery (ANSI/NEDA 24H or IEC R03) Battery life - U1271A/U1272A: 300 hours typical (based on new Alkaline batteries for DC voltage measurement: 30/45/60 hours typical at High/Medium/Low bightness, respectively - Based on new Alkaline batteries for DC voltage measurement: 30/45/60 hours typical at High/Medium/Low bightness, respectively - Based on new Alkaline batteries: 4.4 V (approximately) - For non-rechargeable batteries: 4.4 V (approximately) - For non-rechargeable batteries: 4.5 V (approximately) - 10 × 35 mm 14 n/1000 V 30 k Tast-acting fuse Input impedance at off mode - 1.67 kΩ (protected by positive temperature coefficient resistor) (U1272A, U1273AX: -20 to 55 °C, 0% to 80% RH - U1271A/U1273AX: 40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - - 1.67 kΩ (protected by positive temperature coefficient resistor) (U1272A, U1273AX: -20 to 55 °C, 0% to 80% RH - - 1.10 × 38 mm		33,000 counts)
Solution - U1271A/U1272A: 460 mVA maximum (with backlight enabled) - - U1273A/U1273A: 180 mVA maximum (with maximum brightness) Battery type - 4 × 1.5 V Zinc Choride battery (ANSI/NEDA 240 or IEC R03) or - 4 × 1.5 V Lithium battery (ANSI/NEDA 240 or IEC R03) - - 4 × 1.5 V Lithium battery (ANSI/NEDA 241 or IEC FR03) - - 4 × 1.5 V Lithium battery (ANSI/NEDA 241 or IEC FR03) - - 4 × 1.5 V Lithium battery (ANSI/NEDA 241 or IEC FR03) - - 4 × 1.5 V Lithium battery (ANSI/NEDA 241 or IEC FR03) - - U1273/U1273A: - Based on new Alkaline batteries for DC voltage measurement: : 30/45/60 hours typical at High/Low brightness, respectively - Based on new Likaline batteries: 4.4 V (approximately) - Low battery indicator will fish when the battery voltage drops: - For rechargeable batteries: 4.5 V (approximately) - Low battery 1273 A. and U1273A and U12		 U1273A/U1273AX: Organic LED (OLED) display (with maximum reading of 22,000 counter)
Power consumption - 01271A/01272A: 100 mVA maximum (with maximum brightness) Battery type - 4 × 1.5 V Alkaline battery (ANSI/NEDA 24D or IEC R03), or - 4 × 1.5 V Link understand the settery (ANSI/NEDA 24D or IEC R03) - 4 × 1.5 V Link understand the settery (ANSI/NEDA 24D or IEC R03) Battery life - U1271A/01273AX: 100 mVA maximum (with maximum brightness) Battery life - U1271A and U1272A: 300 hours typical (based on new Alkaline batteries for DC voltage measurement) - U1273AV: 100 mV273AX: - Based on new Alkaline batteries for DC voltage measurement: - Based on new Alkaline batteries for DC voltage measurement: - Based on new Lithum batteries for DC voltage measurement: - 00/100 hours typical at High/Medium/Low brightness, respectively - Based on new Lithum batteries for DC voltage measurement: - 00/100 hours typical at High/Medium/Low brightness, respectively - Low battery indicator will flash when the battery voltage drops: - For non-rechargeable batteries: 4.4 V (approximately) - For rechargeable batteries: 4.4 V (approximately) Fuse - 10 × 38 mm 11 A/1000 V 30 kA fast-acting fuse Input impedance at off mode - 1.87 kΩ (protected by positive temperature coefficient resistor) (U1272A, U1273A, and) Operating environment - Operating temperature: - V1271AV, U1272A, U1273A, and) - 00 °C, 0 to 50% RH - U1273AV, U		
Battery type - 4 × 1.5 V Alkaline battery (ANSI/NEDA 24A or IEC LR03), or - 4 × 1.5 V Zinc Chloride battery (ANSI/NEDA 24D or IEC R03) - 4 × 1.5 V Zinc Chloride battery (ANSI/NEDA 24LF or IEC R03) - 1 × 1.5 V Lithium battery (ANSI/NEDA 24LF or IEC R03) Battery life - U1271A and U1272A: 200 hours typical (based on new Alkaline batteries for DC voltage measurement: 30/45/60 hours typical at High/Low brightness, respectively Based on new Likkline batteries for DC voltage measurement: 30/45/60 hours typical at High/Low brightness, respectively Based on new Likkline batteries for DC voltage measurement: 50/100 hours typical at High/Low brightness, respectively - Based on new Likkline batteries: 4.5 V (approximately) - For non-rechargeable batteries: 4.5 V (approximately) - For non-rechargeable batteries: 4.5 V (approximately) - 10 × 35 mm 440 mA/1000 V 30 kA fast-acting fuse - 10 × 35 mm 440 mA/1000 V 30 kA fast-acting fuse - 10 × 35 mm 440 mA/1000 V 30 kA fast-acting fuse - 10 × 10271A/U1272A/U1273A: -20 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A: -20 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A: -20 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A: -20 to 55 °C, 0% to 80% RH - U1273A/U1272A/U1273A: -20 to 55 °C, 0% to 80% RH - U1273A/U1272A/U1273A: -20 to 55 °C, 0% to 80% RH - U1273A/S: -40 to 55 °C,	Power consumption	 U1273A/U1273AX: 460 mVA maximum (with backlight enabled) U1273A/U1273AX: 180 mVA maximum (with maximum brightness)
- 4 × 1.5 V Zinc Chloride battery (ANSI/NEDA 24D or IEC R03) - 4 × 1.5 V Lithium battery (ANSI/NEDA 24L or IEC R03) Battery life - U1271A and U1272A: 300 hours typical (based on new Alkaline batteries for DC voltage measurement) - U1273A/U1273Ax: - Based on new Alkaline batteries for DC voltage measurement: 30/45/60 hours typical at High/Medium/Low brightness, respectively - Based on new Lithium batteries for DC voltage measurement: 50/100 hours typical at High/Low brightness, respectively - Based on new Lithium batteries for DC voltage measurement: 50/100 hours typical at High/Low brightness, respectively - Based on new Lithium batteries for DC voltage measurement: 50/100 hours typical at High/Low brightness, respectively - Based on new Lithium batteries for DC voltage measurement: 50/100 hours typical at High/Low brightness, respectively - Low battery indicator will flash when the battery voltage drops: - For rechargeable batteries: 4.5 V (approximately) - For rechargeable batteries: 4.5 V (approximately) Fuse - 10 × 35 mm 440 mA/1000 V 30 kA fast-acting fuse Input impedance at off mode - 1.67 kD (protected by positive temperature coefficient resistor) (U1272A, U1273A, and U1273A and U1273A only) Operating environment - Operating temperature: - U1271A/ U1272A/U1273A: -20 to 55 °C, 0% to 80% RH - U1273A/X: -40 to 50 °C, 0% to 80% RH (using Lithium batteries) Full accuracy up to 80% OB	Battery type	 4 × 1.5 V Alkaline battery (ANSI/NEDA 24A or IEC LR03), or
- 4 × 1.5 V Lithium battery (ANSI/NEDA 24LF or IEC FR03) Battery life - U1271A and U1272A: 300 hours typical (based on new Alkaline batteries for DC voltage measurement) - U1273A/U1273AX: - Based on new Alkaline batteries for DC voltage measurement: 30/45/60 hours typical at High/Medium/Low brightness, respectively - Based on new Lithium batteries for DC voltage measurement: 50/100 hours typical at High/Low brightness, respectively - Low battery indicator will flash when the battery voltage drops: - For non-rechargeable batteries: 4.5 V (approximately) Fuse - 10 × 38 mm 410 mA/1000 V 30 kA fast-acting fuse Input impedance at off mode - 1.67 kΩ (protected by positive temperature coefficient resistor) (U1272A, U1273A and U1273AX only) Operating environment - 0perating temperature: - U1271A/ U1272A/U1273A: -20 to 55 °C, 0% to 80% RH - U1271A/ U1272A/U1273A - 20 to 55 °C, 0% to 80% RH - U1271A/ U1272A/U1273A: -20 to 55 °C, 0% to 80% RH - U1271A/ U1272A/U1273A = 00 to 55 °C, 0% to 80% RH - U1271A/ U1272A/U1273A = 00 to 55 °C, 0% to 80% RH Safety compliance - CAN/CSA-C22.2 No. 61010-1-04 - EN/IEC 61010-1:2001 - EN/IEC 61010-1:2004 Measurement category CAT III 1000 V/CAT IV 600 V Electromagnetic compatibility (EMC) Commercial limits compliance with EN61326-1	, ,,	 4 × 1.5 V Zinc Chloride battery (ANSI/NEDA 24D or IEC R03)
Battery life - U1271A and U1272A: 300 hours typical (based on new Alkaline batteries for DC voltage measurement) U1273A/U1273AX: - Based on new Alkaline batteries for DC voltage measurement: 30/45/60 hours typical at High/Medium/Low brightness, respectively - Based on new Lithium batteries for DC voltage measurement: 50/100 hours typical at High/Low brightness, respectively - Based on new Lithium batteries for DC voltage measurement: 50/100 hours typical at High/Low brightness, respectively - Based on new Lithium batteries tor DC voltage measurement: 50/100 hours typical at High/Low brightness, respectively - Boxed on new Lithium batteries tor DC voltage measurement: 50/100 hours typical at High/Low brightness, respectively - Boxed on new Lithium batteries tor DC voltage measurement: 50/100 hours typical at High/Low brightness, respectively - Boxed on new Lithium batteries tor DC voltage measurement: 50/100 hours typical at High/Low brightness, respectively - For rechargeable batteries: 4.5 V (approximately) Fuse - 10 × 35 mm 440 mA/1000 V 30 kA fast-acting fuse Input impedance at off mode - 16.7 kG (portected by positive temperature coefficient resistor) (U1272A, U1273A, U1273A, U1273A, and U1273A, and U1273A, and U1273A, Col to 55 °C, 0% to 80% RH Operating environment - Operating temperature: - U1271A/ U1272A/U1273A; -20 to 55 °C, 0% to 80% RH - Storage compliance - 40 to 70 °C, 0 to 80% RH Storage compliance - 40 to 70 °C, 0 to 80% RH		 4 × 1.5 V Lithium battery (ANSI/NEDA 24LF or IEC FR03)
voltage measurement)U1273A/U1273AX:Based on new Alkaline batteries for DC voltage measurement:30/45/60 hours typical at High/Medium/Low brightness, respectivelyBased on new Lithium batteries for DC voltage measurement:50/100 hours typical at High/Low brightness, respectivelyLow battery indicator will flash when the battery voltage drops:- For non-rechargeable batteries: 4.1 V (approximately)Fuse10 × 35 mm 440 mA/1000 V 30 kA fast-acting fuseInput impedance at off mode- 1.67 kΩ (protected by positive temperature coefficient resistor)(U1272A, U1273A, and U1273AX: -20 to 55 °C, 0% to 80% RH- U1271A/ U1272A/U1273A: -20 to 55 °C, 0% to 80% RH- U1271A/ U1272A/U1273A: -20 to 55 °C, 0% to 80% RH- U1271A/ U1272A/U1273A: -20 to 55 °C, 0% to 80% RH- U1271A/ U1272A/U1273A: -20 to 50 °C, 0% to 80% RH- U1271A/ U1272A/U1273A: -20 to 50 °C, 0% to 80% RH- U1271A/ U1272A/U1273A: -20 to 50 °C, 0% to 80% RH- U1271A/ U1272A/U1273A: -20 to 50 °C, 0% to 80% RH- U1271A/ U1272A/U1273A: -20 to 50 °C, 0% to 80% RH- U1271A/ U1272A/U1273A: -20 to 50 °C, 0% to 80% RH- U1271A/ U1272A/U1273A: -20 to 50 °C, 0% to 80% RH- U1271A/ U1272A/U1273A: -20 to 50 °C, 0% to 80% RH- Storage compliance- CAN/CSA-C22 2.No. 61010-1:04- EN/EC 61010-1:2001- EN/EC 61010-1:2004Measurement categoryCAT III 1000 V/CAT IV 600 VElectromagnetic compatibility (EMC)Commercial limits compliance with EN61326-1Ingress protection ratingIP-54Temperature coeffi	Battery life	- U1271A and U1272A: 300 hours typical (based on new Alkaline batteries for DC
- - 012/34/012/34X: - Based on new Alkaline batteries for DC voltage measurement: 30/45/60 hours typical at High/Medium/Low brightness, respectively - Based on new Lithium batteries for DC voltage measurement: 50/100 hours typical at High/Low brightness, respectively - Low battery indicator will flash when the battery voltage drops: - - For non-rechargeable batteries: 4.5 V (approximately) - For enchargeable batteries: 4.5 V (approximately) - For rechargeable batteries: 4.5 V (approximately) - For sechargeable batteries: 4.5 V (approximately) - For rechargeable batteries: 4.5 V (approximately) - For rechargeable batteries: 4.5 V (approximately) - 10 × 35 mm 440 mA/1000 V 30 kA fast-acting fuse Input impedance at off mode 1.67 kΩ (protected by positive temperature coefficient resistor) (U1272A, U1273A, u1273A, and U1		voltage measurement)
based on new Atkanie batteries to Voltage measurement: 30/45/60 hours typical at High/Low brightness, respectively Based on new Lithium batteries for DC voltage measurement: 50/100 hours typical at High/Low brightness, respectively Low battery indicator will flash when the battery voltage drops: - For non-rechargeable batteries: 4.5 V (approximately) Fuse - 10 × 35 mm 440 m/1000 V 30 kA fast-acting fuse - 10 × 38 mm 11 A/1000 V 30 kA fast-acting fuse - 10 × 38 mm 11 A/1000 V 30 kA fast-acting fuse Input impedance at off mode - 1.67 kΩ (protected by positive temperature coefficient resistor) (U1272A, U1273A and U1273AX only) Operating environment - Operating temperature: - U1271A/ U1272A/U1273A: -20 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH Storage compliance -40 to 70 °C, 0 to 80% RH Safety compliance - CAN/CSA-C22.2 No. 61010-1-04 - EN/IEC 61010-1:2001 - ANSI/UL 61010-1:2004 Measurement category CAT III 1000 V/CAT IV 600 V Electromagnetic compatibility (EMC) Commercial limits compliance with EN61326-1 Ingress protection rating IP-54 Temperature coefficient Ratio (CMRR) > 120 dB at DC, 50/60 Hz ± 0.1% (1 kΩ unbalanced)		 U12/3A/U12/3AX: Based on new Alkaline batteries for DC voltage measurement:
- Based on new Lithium batteries for DC voltage measurement: 50/100 hours typical at High/Low brightness, respectively - Low battery indicator will flash when the battery voltage drops: - For non-rechargeable batteries: 4.4 V (approximately) Fuse - 10 × 35 mm 440 m//1000 V 30 kA fast-acting fuse - 10 × 38 mm 11 A/1000 V 30 kA fast-acting fuse - 10 × 38 mm 11 A/1000 V 30 kA fast-acting fuse Input impedance at off mode - 1.67 kΩ (protected by positive temperature coefficient resistor) (U1272A, U1273A and U1273A and U1273AX only) Operating environment - Operating temperature: - U1271A/ U1272A/U1273A: -20 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 50 °C, 0% to 80% RH - U1273AX: -40 to 50 °C, 0% to 80% RH - U1273AX: -40 to 50 °C, 0% to 80% RH Storage compliance - 40 to 70 °C, 0 to 80% RH - EN/IEC 61010-1:2001 - ANSI/UL 61010-1:2001 - ANSI/UL 61010-1:2004 Measurement category CAT III 1000 V/CAT IV 600 V Electromagnetic compatibility (EMC) Commercial limits compliance with EN61326-1 Ingress protection rating IP-54 Temperature coefficient U1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 x (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C) U1273AX: 0.05 k (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C)		30/45/60 hours typical at High/Medium/I ow brightness, respectively
50/100 hours typical at High/Low brightness, respectivelyLow battery indicator will flash when the battery voltage drops: - For non-rechargeable batteries: 4.4 V (approximately) - For rechargeable batteries: 4.5 V (approximately)Fuse10 × 35 mm 440 mA/1000 V 30 kA fast-acting fuse - 10 × 38 mm 11 A/1000 V 30 kA fast-acting fuseInput impedance at off mode1.67 kΩ (protected by positive temperature coefficient resistor) (U1272A, U1273A and U1273AX -20 to 55 °C, 0% to 80% RH - U1271A/ U1272A/U1273A' -20 to 55 °C, 0% to 80% RH - U1271AX' U1272A/U1273A' -20 to 55 °C, 0% to 80% RH - U1271AX' U1272A/U1273A' -20 to 55 °C, 0% to 80% RH - U1271AX' U1272A/U1273A' -20 to 55 °C, 0% to 80% RH - U1271AX' U1272A/U1273A' -20 to 55 °C, 0% to 80% RH - U1271AX' U1272A/U1273A' -20 to 55 °C, 0% to 80% RH - U1271AX' U1272A/U1273A' -20 to 55 °C, 0% to 80% RH - U1271AX' U1272A/U1273A' -20 to 55 °C, 0% to 80% RH - U1271AX' U1272A/U1273A' -20 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A' -20 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A' -20 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A' -20 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A' -20 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A' -20 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A' -20 to 50 °C, decreasing linearly to 50% RH at 55 °C - Ahtitude up to 3000 meters - Pollution degree IIStorage compliance- 40 to 70 °C, 0 to 80% RHSafety compliance- CAN/CSA-C22.2 No. 61010-1-04 - EN/IEC 61010-1:2001 - ANSI/UL 61010-1:2004Measurement categoryCAT III 1000 V/CAT IV 600 VElectromagnetic compatibility (EMC)Commercial limits compliance with EN61326-1 Ingress protection ratingIngress protection ratingIP-54Temperature coefficientU1271A/U1272A/U1273A': 0.0		 Based on new Lithium batteries for DC voltage measurement:
- Low battery indicator will flash when the battery voltage drops: - For non-rechargeable batteries: 4.4 V (approximately) - For rechargeable batteries: 4.5 V (approximately)Fuse- 10 × 35 mm 440 mA/1000 V 30 kA fast-acting fuse - 10 × 38 mm 11 A/1000 V 30 kA fast-acting fuseInput impedance at off mode- 1.67 kΩ (protected by positive temperature coefficient resistor) (U1272A, U1273A and U1273AX only)Operating environment- Operating temperature: - U1271A/U1272A/U1273A: -20 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C - Adtitude up to 3000 meters - Pollution degree IIStorage compliance- CAN/CSA-C22.2 No. 61010-1-04 - EN/IEC 61010-1:2004Measurement categoryCAT III 1000 V/CAT IV 600 VElectromagnetic compatibility (EMC)Commercial limits compliance with EN61326-1 Ingress protection ratingIP-54Temperature coefficientU1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 x (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C)Common Mode Rejection Ratio (CMRR)> 100 B at 50/60 Hz ± 0.1%		50/100 hours typical at High/Low brightness, respectively
- For non-rechargeable batteries: 4.5 V (approximately) - For rechargeable batteries: 4.5 V (approximately) Fuse - 10 × 35 mm 440 mA/1000 V 30 kA fast-acting fuse Input impedance at off mode - 1.67 kΩ (protected by positive temperature coefficient resistor) (U1272A, U1273A and U1273AX only) Operating environment - Operating temperature: - - U1271A/U1272A/U1273A: -02 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A: -02 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A: -02 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A: -02 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A: -02 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A: -02 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A: -02 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A: -02 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A: -02 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A: -02 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A: -02 to 55 °C, 0% to 80% RH - U1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C, (accreasing linearly to 50% RH at 55 °C) Storage compliance - Altitude up to 3000 meters - Pollution degree II Storage compliance - CAN/CSA-C22.2 No. 61010-1-04 - EN/IEC 61010-1:2001 - Safety compliance - CAN/CSA-C22.2 No. 61010-1-04 - EN/IEC 61010-1:2001 - ANSI/UL 61010-1:2004 Measurement category CAT		 Low battery indicator will flash when the battery voltage drops:
Fuse - 10 × 35 mm 440 mA/1000 V 30 kA fast-acting fuse Input impedance at off mode - 10 × 38 mm 11 A/1000 V 30 kA fast-acting fuse Input impedance at off mode - 1.67 kΩ (protected by positive temperature coefficient resistor) (U1272A, U1273A and U1273AX only) Operating environment - Operating temperature: - U1271A/ U1272A/U1273A: -20 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH Storage compliance -40 to 70 °C, 0 to 80% RH Safety compliance -40 to 70 °C, 0 to 80% RH Safety compliance - CAN/CSA-C22.2 No. 61010-1-04 - EN/IEC 61010-1:2004 Measurement category CAT III 1000 V/CAT IV 600 V Electromagnetic compatibility (EMC) Commercial limits compliance with EN61326-1 Ingress protection rating IP-54 Temperature coefficient U1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) Common Mode Rejection Ratio (CMRR) > 120 dB at DC, 50/60 Hz ± 0.1% (1 kΩ unbalanced)		 For non-rechargeable batteries: 4.4 V (approximately) For rechargeable batteries: 4.5 V (approximately)
Puse= 10 × 35 mill 440 mi/ 1000 V 30 kA fast-acting fuse = 10 × 38 mm 11 A/1000 V 30 kA fast-acting fuse = 10 × 38 mm 11 A/1000 V 30 kA fast-acting fuseInput impedance at off mode= 1.67 kΩ (protected by positive temperature coefficient resistor) (U1272A, U1273A and U1273AX only)Operating environment= 0perating temperature: - U1271A/U1272A/U1273A: -20 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH (using Lithium batteries) - Full accuracy up to 80% RH for temperatures up to 30 °C, decreasing linearly to 500% RH at 55 °C - Altitude up to 3000 meters - Pollution degree IIStorage compliance-40 to 70 °C, 0 to 80% RHSafety compliance- CAN/CSA-C22.2 No. 61010-1-04 - EN/IEC 61010-1:2001 - ANSI/UL 61010-1:2004Measurement categoryCAT III 1000 V/CAT IV 600 VElectromagnetic compatibility (EMC)Commercial limits compliance with EN61326-1Ingress protection ratingIP-54Temperature coefficientU1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 x (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C)Normal Mode Rejection Ratio (CMRR)> 120 dB at DC, 50/60 Hz ± 0.1%		10 x 25 mm //0 mA /1000 V/20 kA fact acting fue
Input impedance at off mode- 1.67 kΩ (protected by positive temperature coefficient resistor) (U1272A, U1273A and U1273AX only)Operating environment- Operating temperature: - U1271A/ U1272A/U1273A: -20 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C - Altitude up to 3000 meters - Pollution degree IIStorage compliance-40 to 70 °C, 0 to 80% RHSafety compliance- CAN/CSA-C22.2 No. 61010-1-04 - EN/IEC 61010-1:2001 - ANSI/UL 61010-1:2004Measurement categoryCAT III 1000 V/CAT IV 600 VElectromagnetic compatibility (EMC)Commercial limits compliance with EN61326-1Ingress protection ratingIP-54Temperature coefficientU1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C)Common Mode Rejection Ratio (CMRR)> 120 dB at DC, 50/60 Hz ± 0.1% (1 kΩ unbalanced)	ruse	-10×38 mm 11 A/1000 V 30 kA fast-acting fuse
(U1272A, U1273A and U1273AX only)Operating environment- Operating temperature: - U1271A/ U1272A/U1273A: -20 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH (using Lithium batteries) - Full accuracy up to 80% RH for temperatures up to 30 °C, decreasing linearly to 50% RH at 55 °C - Altitude up to 3000 meters - Pollution degree IIStorage compliance-40 to 70 °C, 0 to 80% RHSafety compliance- CAN/CSA-C22.2 No. 61010-1-04 - EN/IEC 61010-1:2001 - ANSI/UL 61010-1:2004Measurement categoryCAT III 1000 V/CAT IV 600 VElectromagnetic compatibility (EMC)Commercial limits compliance with EN61326-1 Ingress protection ratingIP-54Temperature coefficientU1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy)/°C (from -40 to 18°C, or 28 to 55°C)Normal Mode Rejection Ration (NMRR)> 60 dB at 50/60 Hz ± 0.1%	Input impedance at off mode	$-1.67 \text{ k}\Omega$ (protected by positive temperature coefficient resistor)
Operating environment- Operating temperature: - U1271A/U1272A/U1273A: -20 to 55 °C, 0% to 80% RH - U1273AX: -40 to 55 °C, 0% to 80% RH (using Lithium batteries) - Full accuracy up to 80% RH for temperatures up to 30 °C, decreasing linearly to 50% RH at 55 °C - Altitude up to 3000 meters - Pollution degree IIStorage compliance-40 to 70 °C, 0 to 80% RHSafety compliance- CAN/CSA-C22.2 No. 61010-1-04 - EN/IEC 61010-1:2001 - ANSI/UL 61010-1:2004Measurement categoryCAT III 1000 V/CAT IV 600 VElectromagnetic compatibility (EMC)Commercial limits compliance with EN61326-1Ingress protection ratingIP-54Temperature coefficientU1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C)Normal Mode Rejection Ratio (NMRR)> 60 dB at 50/60 Hz ± 0.1% (1 kΩ unbalanced)		(U1272A, U1273A and U1273AX only)
 U1271A/ U1272A/U1273A: -20 to 55 °C, 0% to 80% RH U1273AX: -40 to 55 °C, 0% to 80% RH (using Lithium batteries) Full accuracy up to 80% RH for temperatures up to 30 °C, decreasing linearly to 50% RH at 55 °C Altitude up to 3000 meters Pollution degree II Storage compliance -40 to 70 °C, 0 to 80% RH Safety compliance CAN/CSA-C22.2 No. 61010-1-04 EN/IEC 61010-1:2001 ANSI/UL 61010-1:2004 Measurement category CAT III 1000 V/CAT IV 600 V Electromagnetic compatibility (EMC) Commercial limits compliance with EN61326-1 Ingress protection rating IP-54 Temperature coefficient U1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy)/°C (from -40 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy)/°C (from -40 to 18°C, or 28 to 55°C) Common Mode Rejection Ratio (CMRR) > 60 dB at 50/60 Hz ± 0.1% 	Operating environment	 Operating temperature:
- U12/3AX: -40 to 55 °C, 0% to 80% RH (using Lithium batteries)- Full accuracy up to 80% RH for temperatures up to 30 °C, decreasing linearly to 50% RH at 55 °C- Altitude up to 3000 meters - Pollution degree IIStorage compliance-40 to 70 °C, 0 to 80% RHSafety compliance- CAN/CSA-C22.2 No. 61010-1-04 - EN/IEC 61010-1:2001 - ANSI/UL 61010-1:2004Measurement categoryCAT III 1000 V/CAT IV 600 VElectromagnetic compatibility (EMC)Commercial limits compliance with EN61326-1Ingress protection ratingIP-54Temperature coefficientU1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C)Common Mode Rejection Ratio (CMRR)> 120 dB at DC, 50/60 Hz ± 0.1% (1 kΩ unbalanced)Normal Mode Rejection Ration (NMRR)> 60 dB at 50/60 Hz ± 0.1%		- U1271A/ U1272A/U1273A: -20 to 55 °C, 0% to 80% RH
Full accuracy up to 30% km for temperatures up to 30° C, decreasing linearly to 50% RH at 55 °C – Altitude up to 3000 meters – Pollution degree IIStorage compliance-40 to 70 °C, 0 to 80% RHSafety compliance- CAN/CSA-C22.2 No. 61010-1-04 – EN/IEC 61010-1:2001 – ANSI/UL 61010-1:2004Measurement categoryCAT III 1000 V/CAT IV 600 VElectromagnetic compatibility (EMC)Commercial limits compliance with EN61326-1Ingress protection ratingIP-54Temperature coefficientU1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 x (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C)Common Mode Rejection Ratio (CMRR)> 120 dB at DC, 50/60 Hz ± 0.1% (1 kΩ unbalanced)		 U12/3AX: -40 to 55 °C, 0% to 80% KH (using Lithium batteries) Full accuracy up to 20% RH for temperatures up to 20 °C, decreasing linearly to
- Altitude up to 3000 meters - Pollution degree IIStorage compliance-40 to 70 °C, 0 to 80% RHSafety compliance- CAN/CSA-C22.2 No. 61010-1-04 - EN/IEC 61010-1:2001 - ANSI/UL 61010-1:2004Measurement categoryCAT III 1000 V/CAT IV 600 VElectromagnetic compatibility (EMC)Commercial limits compliance with EN61326-1Ingress protection ratingIP-54Temperature coefficientU1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C)Common Mode Rejection Ratio (CMRR)> 120 dB at DC, 50/60 Hz ± 0.1% (1 kΩ unbalanced)Normal Mode Rejection Ration (NMRR)> 60 dB at 50/60 Hz ± 0.1%		50% RH at 55 °C
- Pollution degree IIStorage compliance-40 to 70 °C, 0 to 80% RHSafety compliance- CAN/CSA-C22.2 No. 61010-1-04 - EN/IEC 61010-1:2001 - ANSI/UL 61010-1:2004Measurement categoryCAT III 1000 V/CAT IV 600 VElectromagnetic compatibility (EMC)Commercial limits compliance with EN61326-1Ingress protection ratingIP-54Temperature coefficientU1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C)Common Mode Rejection Ratio (CMRR)> 120 dB at DC, 50/60 Hz ± 0.1% (1 kΩ unbalanced)Normal Mode Rejection Ration (NMRR)> 60 dB at 50/60 Hz ± 0.1%		 Altitude up to 3000 meters
Storage compliance-40 to 70 °C, 0 to 80% RHSafety compliance- CAN/CSA-C22.2 No. 61010-1-04 - EN/IEC 61010-1:2001 - ANSI/UL 61010-1:2004Measurement categoryCAT III 1000 V/CAT IV 600 VElectromagnetic compatibility (EMC)Commercial limits compliance with EN61326-1Ingress protection ratingIP-54Temperature coefficientU1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C)Common Mode Rejection Ratio (CMRR)> 120 dB at DC, 50/60 Hz ± 0.1% (1 kΩ unbalanced)Normal Mode Rejection Ration (NMRR)> 60 dB at 50/60 Hz ± 0.1%		- Pollution degree II
Safety compliance- CAN/CSA-C22.2 No. 61010-1-04 - EN/IEC 61010-1:2001 - ANSI/UL 61010-1:2004Measurement categoryCAT III 1000 V/CAT IV 600 VElectromagnetic compatibility (EMC)Commercial limits compliance with EN61326-1Ingress protection ratingIP-54Temperature coefficientU1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C)Common Mode Rejection Ratio (CMRR)> 120 dB at DC, 50/60 Hz ± 0.1% (1 kΩ unbalanced)Normal Mode Rejection Ration (NMRR)> 60 dB at 50/60 Hz ± 0.1%	Storage compliance	-40 to 70 °C, 0 to 80% RH
- EN/IEC 61010-1:2001 - ANSI/UL 61010-1:2004 Measurement category CAT III 1000 V/CAT IV 600 V Electromagnetic compatibility (EMC) Commercial limits compliance with EN61326-1 Ingress protection rating IP-54 Temperature coefficient U1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 x (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C) Common Mode Rejection Ratio (CMRR) > 120 dB at DC, 50/60 Hz ± 0.1% (1 kΩ unbalanced) Normal Mode Rejection Ration (NMRR) > 60 dB at 50/60 Hz ± 0.1%	Safety compliance	- CAN/CSA-C22.2 No. 61010-1-04
— ANSI/OL 61010-1:2004 Measurement category CAT III 1000 V/CAT IV 600 V Electromagnetic compatibility (EMC) Commercial limits compliance with EN61326-1 Ingress protection rating IP-54 Temperature coefficient U1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 x (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C) Common Mode Rejection Ratio (CMRR) > 120 dB at DC, 50/60 Hz ± 0.1% (1 kΩ unbalanced) Normal Mode Rejection Ration (NMRR) > 60 dB at 50/60 Hz ± 0.1%		- EN/IEC 61010-1:2001
Measurement category CAT III 1000 V/CAT IV 600 V Electromagnetic compatibility (EMC) Commercial limits compliance with EN61326-1 Ingress protection rating IP-54 Temperature coefficient U1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C) Common Mode Rejection Ratio (CMRR) > 120 dB at DC, 50/60 Hz ± 0.1% (1 kΩ unbalanced) Normal Mode Rejection Ration (NMRR) > 60 dB at 50/60 Hz ± 0.1%		- ANSI/ UL 61010-1:2004
Electromagnetic compatibility (EMC) Commercial limits compliance with EN61326-1 Ingress protection rating IP-54 Temperature coefficient U1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from –20 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy/ °C (from –40 to 18°C, or 28 to 55°C) Common Mode Rejection Ratio (CMRR) > 120 dB at DC, 50/60 Hz ± 0.1% (1 kΩ unbalanced) Normal Mode Rejection Ration (NMRR) > 60 dB at 50/60 Hz ± 0.1%	Measurement category	
Ingress protection ratingIP-54Temperature coefficientU1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C)Common Mode Rejection Ratio (CMRR)> 120 dB at DC, 50/60 Hz ± 0.1% (1 kΩ unbalanced)Normal Mode Rejection Ration (NMRR)> 60 dB at 50/60 Hz ± 0.1%	Electromagnetic compatibility (EMC)	Commercial limits compliance with EN61326-1
Temperature coefficientU1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from -20 to 18°C, or 28 to 55°C) U1273AX: 0.05 × (specified accuracy/ °C (from -40 to 18°C, or 28 to 55°C)Common Mode Rejection Ratio (CMRR)> 120 dB at DC, 50/60 Hz ± 0.1% (1 kΩ unbalanced)Normal Mode Rejection Ration (NMRR)> 60 dB at 50/60 Hz ± 0.1%	Ingress protection rating	IP-54
Common Mode Rejection Ratio (CMRR) > 120 dB at DC, 50/60 Hz ± 0.1% (1 kΩ unbalanced) Normal Mode Rejection Ration (NMRR) > 60 dB at 50/60 Hz ± 0.1%	Temperature coefficient	U1271A/U1272A/U1273A: 0.05 × (specified accuracy)/°C (from –20 to 18°C, or 28 to 55°C) U1273AX: 0.05 x (specified accuracy/ °C (from –40 to 18°C, or 28 to 55°C)
Normal Mode Rejection Ration (NMRR) $> 60 \text{ dB}$ at 50/60 Hz $\pm 0.1\%$	Common Mode Rejection Ratio (CMRR)	$>$ 120 dB at DC, 50/60 Hz \pm 0.1% (1 k Ω unbalanced)
	Normal Mode Rejection Ration (NMRR)	> 60 dB at 50/60 Hz ± 0.1%
Dimensions (W x H x D) 92 × 207 × 59 mm	Dimensions (W x H x D)	92 × 207 × 59 mm
Weight – U1271A: 518 grams (with batteries)	Weight	- U1271A: 518 grams (with batteries)
 U1272A: 520 grams (with batteries) 		 U1272A: 520 grams (with batteries)
 U1273A: 500 grams (with batteries) 		 U1273A: 500 grams (with batteries) U1272AX: E00 grams (with batteries)
- UIZ/JAX: DUU grams (WITH DATTERIES)	14/ .	- U12/JAA: DUU grams (With Datteries)
vvarranty – Three years for product – Three months for product's accessories	vvarranty	 Inree years for product Three months for product's accessories
Calibration cycle One year	Calibration cycle	One year

Specification Assumptions

- Accuracy is given as \pm (% of reading + counts of least significant digit) at 23 °C \pm 5 °C, with relative humidity less than 80% RH.
- AC V and AC μA/mA/A specifications are AC coupled, true RMS and are valid from 5% of range to 100% of range.
- The crest factor may be up to 3.0 at full scale except for the 1000 V range where it is 1.5 at full scale.
- For non-sinusoidal waveforms, add (2% reading + 2% full scale) typical, for crest factors up to 3.
- After Z_{LOW} voltage measurements, wait at least 20 minutes for thermal impact to cool before proceeding with any other measurement.

DC specifications for U1271A, U1272A, U1273A and U1273AX

Function Range		Resolution		Accuracy ± (% of react counts of least signific	Accuracy ± (% of reading + counts of least significant digit)		
			U1271A	U1272A	U1273A/U1273AX	Burden voltage	
	30 mV	0.001 mV	_	0.05 + 20	0.05 + 20	_	
	300 mV	0.01 mV	0.05 + 5	0.05 + 5	0.05 + 5	_	
	3 V	0.0001 V	0.05 + 5	0.05 + 5	0.05 + 5		
	30 V	0.001 V	0.05 + 2	0.05 + 2	0.05 + 2		
	300 V	0.01 V	0.05 + 2	0.05 + 2	0.05 + 2	_	
	1000 V	0.1 V	0.05 + 2	0.05 + 2	0.05 + 2	—	
Voltage ¹	Z _{LOW} (low input impedance) enabled, applicable for 1000 V range and resolution only	0.1 V		1 + 20	1 + 20	_	
	30 Ω	0.001 Ω		0.2 + 10	0.2 + 10	0.65 mA	
-	300 Ω	0.01 Ω	0.2 + 5	0.2 + 5	0.2 + 5	0.65 mA	
	3 kΩ	0.0001 kΩ	0.2 + 5	0.2 + 5	0.2 + 5	65 µA	
	30 kΩ	0.001 kΩ	0.2 + 5	0.2 + 5	0.2 + 5	6.5 µA	
	300 kΩ	0.01 kΩ	0.2 + 5	0.2 + 5	0.2 + 5	0.65 µA	
Resistance ²	3 MΩ	0.0001 MΩ	0.6 + 5	0.6 + 5	0.6 + 5	93 nA/10 MΩ	
	30 MΩ	0.001 MΩ	1.2 + 5	1.2 + 5	1.2 + 5	93 nA/10 MΩ	
	100 MΩ	0.01 MΩ	2.0 +10			93 nA/10 MΩ	
	300 MΩ	0.01 MΩ	—	2.0 + 10 @ < 100 MΩ 8.0 + 10 @ > 100 MΩ	2.0 + 10 @ < 100 MΩ 8.0 + 10 @ > 100 MΩ	93 nA/10 MΩ	
	300 nS	0.01 nS	1 + 10	1 + 10	1 + 10	93 nA/10 MΩ	
	300 µA	0.01 µA	0.2 + 5	0.2 + 3	0.2 + 5	< 0.04 V/100 Ω	
	3000 µA	0.1 µA	0.2 + 5	0.2 + 3	0.2 + 5	< 0.4 V/100 Ω	
Current ³	30 mA	0.001 mA	0.2 + 5	0.2 + 3	0.2 + 5	< 0.08 V/1 Ω	
Current [。] –	300 mA	0.01 mA	0.2 + 5	0.2 + 3	0.2 + 5	< 1.00 V/1 Ω	
	3 A	0.0001 A	0.3 +10	0.3 +10	0.3 +10	< 0.1 V/0.01 Ω	
	10 A	0.001 A	0.3 +10	0.3 +10	0.3 +10	< 0.3 V/0.01 Ω	
Diodo Tos+4	3 V	0.0001 V	0.5 + 5	0.5 + 5	0.5 + 5	Approximately 1 to 2 mA	
DIDUE LESL	Auto	0.0001 V	_	0.5 + 5	0.5 + 5	Approximately 0.1 to 0.3 mA	

See notes on next page.

Notes for DC specifications (previous page)

- 1. Notes for voltage specifications:
 - The accuracy of the 30 to 300 mV range is specified after the Null function is used to subtract the thermal effect (by shorting the test leads).
 - For Z_{LOW} measurements, autoranging is disabled and the multimeter's range is set to 1000 volts in the manual ranging mode.
- 2. Notes for resistance specifications:
 - Overload protection: 1000 Vrms for short circuits with < 0.3 A current.
 - Maximum open voltage is < +3.3 V.
 - Built-in buzzer beeps when the resistance measured is less than 25 Ω ± 10 Ω. The multimeter can capture intermittent measurements longer than 1 ms.
 - The accuracy of the 300 Ω to 3 kΩ range is specified after the Null function is used to subtract the test lead resistance and thermal effect (by shorting the test leads).
 - U1273AX only: The accuracy for all resistance ranges is specified after the Null function is used when measuring at temperatures below -20 °C. The Null function is used to subtract the test lead resistance and thermal effect (by shorting the test leads).
 - For the ranges of 30 M Ω and 100 M Ω , the RH is specified for < 60%.
 - The accuracy for ranges < 50 nS is specified after the Null function is used on an open test lead.
 - The temperature coefficient of the 100 MΩ and 300 MΩ range is 0.1 × (specified accuracy)/°C (from -40 to 18 °C or 28 to 55 °C).
- 3. Notes for current specifications:
 - Overload protection for 300 μA to 300 mA range: 0.44 A/1000 V; 10 × 35 mm 30 kA fast-acting fuse.
 - Overload protection for 3 A to 10 A range: 11 A/1000 V; 10 × 38 mm 30 kA fast-acting fuse.
 - Specification for 300 mA range: 440 mA continuous.
 - Specification for 10 A range: 10 A continuous. Add 0.3% to the specified accuracy when measuring signals > 10 to 20 A for 30 seconds
 maximum. After measuring currents > 10 A, cool down the multimeter for twice the duration of the measured time before proceeding with low
 current measurements.
- 4. Notes for diode specifications:
 - Overload protection: 1000 Vrms for short circuits with < 0.3 A current.
 - Built-in buzzer beeps continuously when the voltage measured is less than 50 mV and beeps once for forward-biased diode or semiconductor junctions measured between 0.3 V and 0.8 V (0.3 V ≤ reading ≤ 0.8 V).
 - Open voltage for diode: < +3.3 V DC.
 - Open voltage for Auto diode: < +2.5 V DC and > -1.0 V DC.

AC specifications for U1271A

			Accu	racy ± (% of reading + count	s of least significa	nt digit)
Function	Range	Resolution	45 Hz to 65 Hz	30 Hz to 1 kHz	1 kHz to 5 kHz	5 kHz to 20 kHz
	300 mV	0.01 mV	0.7 + 20	1.0 + 25	2.0 + 25	2.0 + 40
-	3 V	0.0001 V	0.7 + 20	1.0 + 25	2.0 + 25	2.0 + 40
	30 V	0.001 V	0.7 + 20	1.0 + 25	2.0 + 25	2.0 + 40
True RMS AC	300 V	0.01 V	0.7 + 20	1.0 + 25	2.0 + 25	—
Voltage ¹	1000 V	0.1 V	0.7 + 20	1.0 + 25	_	_
	LPF (low pass filter) enabled, applicable for all voltage ranges and resolution		0.7 + 20	1.0 + 25 @ < 200 Hz 5.0 + 25 @ < 440 Hz	—	—

Function	Range	Resolution	Accuracy ± (% of reading + counts of least significant digit) 45 Hz to 2 kHz	Burden voltage/Shunt
	300 µA	0.01 µA	0.9 + 25	< 0.04 V/100 Ω
- True RMS AC	3000 µA	0.1 µA	0.9 + 25	< 0.4 V/100 Ω
	30 mA	0.001 mA	0.9 + 25	< 0.08 V/1 Ω
Current ²	300 mA	0.01 mA	0.9 + 25	< 1.00 V/1 Ω
-	3 A	0.0001 A	1.0 + 25	< 0.1 V/0.01 Ω
	10 A	0.001 A	1.0 + 25	< 0.3 V/0.01 Ω

1. Notes for voltage specifications:

- Overload protection: 1000 Vrms. For millivolt measurements, 1000 Vrms for short circuits with < 0.3 A current.

- Input impedance: $10 \text{ M}\Omega$ (nominal) in parallel with < 100 pF.
- 2. Notes for current specifications:
 - Overload protection for 300 μA to 300 mA range: 0.44 A/1000 V; 10 × 35 mm 30 kA fast-acting fuse.
 - Overload protection for 3 A to 10 A range: 11 A/1000 V; 10 × 38 mm 30 kA fast-acting fuse.
 - Specification for 300 mA range: 440 mA continuous.
 - Specification for 10 A range: 10 A continuous. Add 0.3% to the specified accuracy when measuring signals > 10 to 20 A for 30 seconds maximum. After measuring currents > 10 A, cool down the multimeter for twice the duration of the measured time before proceeding with low current measurements.

			А	ccuracy ± (% of reading -	+ counts of lea	st significant di	git)
Function	Range	Resolution	45 Hz to 65 Hz	20 Hz to 1 kHz	1 kHz to 5 kHz	5 kHz to 20 kHz	20 kHz to 100 kHz
	30 mV	0.001 mV	0.6 + 20	0.7 + 25	1.0 + 25	1.0 + 40	3.5 + 40
	300 mV	0.01 mV	0.6 + 20	0.7 + 25	1.0 + 25	1.0 + 40	3.5 + 40
	3 V	0.0001 V	0.6 + 20	1.0 + 25	1.5 + 25	2.0 + 40	3.5 + 40
	30 V	0.001 V	0.6 + 20	1.0 + 25	1.5 + 25	2.0 + 40	3.5 + 40
Voltage ¹	300 V	0.01 V	0.6 + 20	1.0 + 25	1.5 + 25	2.0 + 40	_
-	1000 V	0.1 V	0.6 + 20	1.0 + 25	1.5 + 25	_	_
	LPF (low pas applicable ranges ar	LPF (low pass filter) enabled, applicable for all voltage ranges and resolution		1.0 + 25 @ < 200 Hz 5.0 + 25 @ < 440 Hz	—	—	—
	ZLOW	1000 V	2.0 + 40	2 + 40 @ < 440 Hz		_	_

AC specifications for U1272A/U1273A and U1273AX

Function	Range	Resolution	Accuracy ± (% counts of least s	Burden voltage/Shunt	
			45 Hz to 65 Hz	20 Hz to 2 kHz	
	300 µA	0.01 µA	0.6 + 25	0.9 + 25	< 0.04 V/100 Ω
True RMS AC Current ²	3000 µA	0.1 µA	0.6 + 25	0.9 + 25	< 0.4 V/100 Ω
	30 mA	0.001 mA	0.6 + 25	0.9 + 25	< 0.08 V/1 Ω
	300 mA	0.01 mA	0.6 + 25	0.9 + 25	< 1.00 V/1 Ω
	3 A	0.0001 A	0.8 + 25	1.0 + 25	< 0.1 V/0.01 Ω
	10 A	0.001 A	0.8 + 25	1.0 + 25	< 0.3 V/0.01 Ω

1. Notes for voltage specifications:

- Overload protection: 1000 Vrms. For millivolt measurements, 1000 Vrms for short circuits with < 0.3 A current.

- Input impedance: $10 \text{ M}\Omega$ (nominal) in parallel with < 100 pF.
- Z_{LOW} impedance: 2 k Ω (nominal).
- The input signal is lower than the product of 20,000,000 V×Hz.
- For 20 to 100 kHz accuracy: Three counts of the LSD per kHz of additional error is to be added for frequencies > 20 kHz and signal inputs < 10% of range.
- U1273AX only: For all AC voltage ranges, the accuracy is specified at 2.5% + 25 counts when measuring below -20 °C for 20 to 45 Hz AC signals.
- 2. Notes for current specifications:
 - Overload protection for 300 μA to 300 mA range: 0.44 A/1000 V; 10 × 35 mm 30 kA fast-acting fuse.
 - Overload protection for 3 A to 10 A range: 11 A/1000 V; 10 × 38 mm 30 kA fast-acting fuse.
 - Specification for 300 mA range: 440 mA continuous.
 - Specification for 10 A range: 10 A continuous. Add 0.3% to the specified accuracy when measuring signals > 10 to 20 A for 30 seconds maximum. After measuring currents > 10 A, cool down the multimeter for twice the duration of the measured time before proceeding with low current measurements.
 - U1273AX only: The accuracy for the 300 µA range, 3000 µA range, and 30 mA is specified after the Null function is used when measuring at temperatures below -20 °C. The Null function is used to subtract the test lead resistance and thermal effect (by shorting the test leads).
 - U1273AX only: For all AC current ranges, the accuracy is specified at 2.5% + 25 counts when measuring below -20 °C for 20 to 45 Hz AC signals.

			Accuracy ± (% of reading + counts of least significant digit)					
Function	Range	Resolution	45 Hz to 65 Hz	20 Hz to 1 kHz	1 kHz to 5 kHz	5 kHz to 20 kHz	20 kHz to 100 kHz	
	30 mV	0.001 mV	0.7 + 40	0.8 + 45	1.1 + 45	1.1 + 60	3.6 + 60	
	300 mV	0.01 mV	0.7 + 25	0.8 + 30	1.1 + 30	1.1 + 45	3.6 + 45	
True RMS AC + DC Voltage ¹	3 V	0.0001 V	0.7 + 25	1.1 + 30	1.6 + 30	2.1 + 45	3.6 + 45	
	30 V	0.001 V	0.7 + 25	1.1 + 30	1.6 + 30	2.1 + 45	3.6 + 45	
	300 V	0.01 V	0.7 + 25	1.1 + 30	1.6 + 30	2.1 + 45	_	
	1000 V	0.1 V	0.7 + 25	1.1 + 30	1.6 + 30		_	

AC + DC specifications for U1272A/U1273A and U1273AX

Function	Range	Resolution	Burden voltage/Shunt		
			45 Hz to 65 Hz	20 Hz to 2 kHz	
	300 µA	0.01 µA	0.8 + 30	1.1 + 30	< 0.04 V/100 Ω
True RMS — AC + DC — Current ² —	3000 µA	0.1 µA	0.8 + 30	1.1 + 30	< 0.4 V/100 Ω
	30 mA	0.001 mA	0.8 + 30	1.1 + 30	< 0.08 V/1 Ω
	300 mA	0.01 mA	0.8 + 30	1.1 + 30	< 1.00 V/1 Ω
	3 A	0.0001 A	0.9 + 35	1.3 + 35	< 0.1 V/0.01 Ω
	10 A	0.001 A	0.9 + 35	1.3 + 35	< 0.3 V/0.01 Ω

1. Notes for voltage specifications:

- Overload protection: 1000 Vrms. For millivolt measurements, 1000 Vrms for short circuits with < 0.3 A current.
- Input impedance: $10 \text{ M}\Omega$ (nominal) in parallel with < 100 pF.
- For 20 to 100 kHz accuracy: Three counts of the LSD per kHz of additional error is to be added for frequencies > 20 kHz and signal inputs < 10% of range.
- U1273AX only: For all AC+DC voltage ranges, the accuracy is specified at 2.5% + 30 counts when measuring below –20 °C for 20 to 45 Hz AC+DC signals.
- 2. Notes for current specifications:
 - Overload protection for 300 μ A to 300 mA range: 0.44 A/1000 V; 10 \times 35 mm 30 kA fast-acting fuse.
 - Overload protection for 3 A to 10 A range: 11 A/1000 V; 10 × 38 mm 30 kA fast-acting fuse.
 - Specification for 300 mA range: 440 mA continuous.
 - Specification for 10 A range: 10 A continuous. Add 0.3% to the specified accuracy when measuring signals > 10 to 20 A for 30 seconds maximum. After measuring currents > 10 A, cool down the multimeter for twice the duration of the measured time before proceeding with low current measurements.
 - U1273AX only: The accuracy for the 300 μA range, 3000 μA range, and 30 mA is specified after the Null function is used when measuring at temperatures below –20 °C. The Null function is used to subtract the test lead resistance and thermal effect (by shorting the test leads).
 - U1273AX only: For all AC+DC current ranges, the accuracy is specified at 2.5% + 30 counts when measuring below -20 °C for 20 to 45 Hz AC+DC signals.

Thermocouple	Range	Resolution	Accuracy ± (% of reading + as specified below)		
туре			U1271A	U1272A	U1273A/U1273AX
K	–200 to 1372 °C	0.1 °C	1% of reading + 1 °C	1% of reading + 1 °C	1% of reading + 1 °C
К —	–328 to 2502 °F	0.1 °F	1% of reading + 1.8 °F	1% of reading + 1.8 °F	1% of reading + 1.8 °F
	–210 to 1200 °C	0.1 °C	_	1% of reading + 1 °C	1% of reading + 1 °C
J	-346 to 2192 °F	0.1 °F	_	1% of reading + 1.8 °F	1% of reading + 1.8 °F

Temperature specifications¹⁻⁶

1. The specifications above is specified after 60 minutes of warm-up time.

2. The accuracy does not include the tolerance of the thermocouple probe.

3. Do not allow the temperature sensor to contact a surface that is energized above 30 Vrms or 60 V DC. Such voltages pose a shock hazard.

4. Ensure that the ambient temperature is stable within ±1 °C and that the Null function is used to reduce the test lead's thermal effect and temperature offset. Before using Null function, set the multimeter to measure temperature without ambient compensation (°C) and keep the thermocouple probe as close to the multimeter as possible (avoid contact with any surface that has a different temperature from the ambient temperature).

- 5. When measuring temperature with respect to any temperature calibrator, try to set both the calibrator and multimeter with an external reference (without internal ambient compensation). If both the calibrator and multimeter are set with internal reference (with internal ambient compensation), some deviations may show between the readings of the calibrator and multimeter, due to differences in ambient compensation between the calibrator and multimeter. Keeping the multimeter close to the output terminal of calibrator will help reduce the deviation.
- 6. The temperature calculation is specified according to the safety standards of EN/IEC-60548-1 and NIST175.

Range	Resolution	Accuracy ± (% of reading + counts of least significant digit)		
		U1271A	U1272A	U1273A/U1273AX
10 nF	0.001 nF	1 + 5	1 + 5	1 + 5
100 nF	0.01 nF	1 + 2	1 + 2	1 + 2
1000 nF	0.1 nF	1 + 2	1 + 2	1 + 2
10 µF	0.001 µF	1 + 2	1 + 2	1 + 2
100 µF	0.01 µF	1 + 2	1 + 2	1 + 2
1000 µF	0.1 µF	1 + 2	1 + 2	1 + 2
10 mF	0.001 mF	1 + 2	1 + 2	1 + 2

Capacitance specifications^{7, 8}

7. Overload protection: 1000 Vrms for short circuits with < 0.3 A current.

8. The accuracy for all ranges is specified based on a film capacitor or better, and after the Null function is used to subtract the test lead resistance and thermal effect (by shorting the test leads).

Frequency specifications^{1, 2}

Range	Resolution	Accuracy ± (% of reading + counts of least significant digit)	Minimum input frequency
99.999 Hz	0.001 Hz	0.02 + 5	
999.99 Hz	0.01 Hz	0.005 + 5	
9.9999 kHz	0.1 Hz	0.005 + 5	
99.999 kHz	1 Hz	0.005 + 5	0.5 HZ
999.99 kHz	0.01 kHz	0.005 + 5	
> 1 MHz	0.1 kHz	0.005 + 5 @ < 1 MHz	

1. Overload protection: 1000 V; input signal is < 20,000,000 V × Hz (product of voltage and frequency).

2. The frequency measurement is susceptible to error when measuring low-voltage, low-frequency signals. Shielding inputs from external noise pickup is critical for minimizing measurement errors. Turning on the low pass filter may help you to filter out the noise and achieve a stable reading.

Duty Cycle³

Mode	Range	Accuracy at full scale
DC coupling	99.99%	0.3 % per kHz + 0.3 %
AC coupling	99.99%	0.3 % per kHz + 0.3 %

3. Notes for duty cycle specifications:

The accuracy for duty cycle and pulse width measurements is based on a 3 V square wave input to the DC 3 V range. For AC couplings, the duty cycle range can be measured within the range of 10% to 90% for signal frequencies > 20 Hz.

- The range of the duty cycle is determined by the frequency of the signal: {10 μs × frequency × 100%} to {[1 - (10 μs × frequency)] × 100%}.

- The pulse width (positive or negative) must be > 10 μs. The range of the pulse width is determined by the frequency of the signal.

Pulse Width⁴

Range	Resolution	Accuracy at full scale
999.99 ms	0.01 ms	(duty cycle accuracy/frequency) + 0.01 ms
2000.0 ms	0.1 ms	(duty cycle accuracy/frequency) + 0.1 ms

4. Notes for pulse width specifications:

- The accuracy for duty cycle and pulse width measurements is based on a 3 V square wave input to the DC 3 V range.

- The pulse width (positive or negative) must be > 10 μs. The range of the pulse width is determined by the frequency of the signal.

	Minimum sensitivity (RMS sine wave)			Trigger level fo	or DC coupling
Input range	15 Hz to	0.5 Hz to	Up to	0.5 Hz to	200 kHz
	100 kHz	200 kHz	1 MHz	U1271A	U1272A
30 mV	3 mV	3 mV	—	—	5 mV
300 mV	6 mV	8 mV	40 mV	10 mV	15 mV
3 V	0.12 V	0.2 V	0.4 V	0.15 V	0.15 V
30 V	0.6 V	0.8 V	2.6 V	1.5 V	1.5 V
300 V	6 V	8 V @ < 100 kHz	_	9 V @ < 100 kHz	9 V @ < 100 kHz
1000 V	50 V	50 V @ < 100 kHz		90 V @ < 100 kHz	90 V @ < 100 kHz

U1271A and U1272A frequency sensitivity for voltage measurements^{1, 2, 3}

1. Maximum input for specified accuracy, refer to "AC specifications" on page 12.

2. 30 mV range applicable for U1272A only.

3. 200 kHz to 1 MHz range applicable for U1272A only.

U1273A/U1273AX sensitivity for voltage measurements⁴

lanut range	Frequency sensitivity and trigger level				
input range	Minimu	n sensitivity (RMS sii	ne wave)	Trigger level for DC coupling	
Maximum input for specified accuracy, refer to AC voltage	15 Hz to 100 kHz	0.5 Hz to 200 kHz	Up to 1 MHz	0.5 Hz to 200 kHz	
30 mV	3 mV	3 mV		5 mV	
300 mV	7 mV	8 mV	38 mV	15 mV	
3 V	0.12 V	0.12 V	0.48 V	0.15 V	
30 V	0.8 V	0.8 V	3.5 V	1.5 V	
300 V	6.7 V	8 V < 100 kHz	—	11 V < 100 kHz	
1000 V	67 V	67 V < 100 kHz	_	110 V < 100 kHz	

4. Maximum input for specified accuracy, refer to "AC specifications" on page 13.

Frequency sensitivity for current measurements⁵

	Minimum sensitivi	ty (RMS sine wave)	
Input range	2 Hz to 30 kHz		
	U1271A/U1272A	U1273A/U1273AX	
300 µA	100 µA	70 μA	
3000 µA	70 µA	120 µA	
30 mA	1.2 mA	1.2 mA	
300 mA	12 mA	12 mA	
3 A	0.12 A	0.12 A	
10 A	1.2 A	1.2 A	

5. Maximum input for specified accuracy, refer to "AC specifications" on page 12 and 13.

Peak hold

Signal width	Accuracy for DC Voltage and Current
Single event >1 ms	Specified accuracy + 400
Repetitive >250 µs	Specified accuracy + 1000

Decibel (dB) for U1272A and U1273A^{1, 2, 3}

dB base	Reference	Default reference
1 mW (dBm)	1 to 9999 Ω	50 Ω
1 V (dBV)	1 V	1 V

1. The reading of dBm is indicated in decibels of power above or below 1 mW, or decibels of voltage above or below 1 V. The formula is calculated according to the voltage measurement and specified reference impedance. Its accuracy is depended on the accuracy of the voltage measurement. See Decibel (dBV) accuracy table below.

2. Auto-ranging mode is used.

3. The bandwidth is according to voltage measurement.

Decibel (dBV) accuracy

dBV range		Accuracy					
Range	Minimum	Maximum	45 Hz to 65 Hz	20 Hz to 1 kHz	1 Hz to 5 kHz	5 kHz to 20 kHz	20 Hz to 100 kHz
30 mV	-56.48	-30.46	0.06	0.07	0.09	0.1	0.32
300 mV	-36.48	-10.46	0.06	0.07	0.09	0.1	0.32
3 V	-16.48	+9.54	0.06	0.09	0.14	0.19	0.32
30 V	+3.52	+29.54	0.06	0.09	0.14	0.19	0.32
300 V	+23.52	+49.54	0.06	0.09	0.14	0.19	—
1000 V	+33.98	+60	0.06	0.09	0.14	—	—

Measurement rate (approximate)

Function	Times/second			
Function	U1271A	U1272A/U1273A/U1273AX		
ACV	7	7		
DCV	7	7		
Ω	14	14		
Ω with offset compensation	-	3		
Diode	14	14		
Auto Diode	-	3		
Capacitance	4 (< 100 μF)	4 (< 100 μF)		
DCA	7	7		
ACA	7	7		
Temperature	7	7		
Frequency	2 (> 10 Hz)	2 (> 10 Hz)		
Duty cycle	1 (> 10 Hz)	1 (> 10 Hz)		
Pulse width	1 (> 10 Hz)	1 (> 10 Hz)		

Ordering Information



Standard shipped accessories

Standard test leads, test probes with 4-mm tips, K-type thermocouple and adapter, 4x AAA alkaline batteries (4x AAA lithium batteries for U1273AX only), Certificate of Calibration, UK 6 (test report), Quick Start Guide

Optional accessories

Measuring accessories (non-temperature)

U1161A Extended test lead kit		Includes two test leads (red and black), two test probes, medium- sized alligator clips and 4-mm banana plugs. – Test leads: CAT III 1000 V, CAT IV 600 V, 15 A – Test probes (4-mm tips): CAT III 1000 V, CAT IV 600 V, 15 A – Medium-sized alligator clips: CAT III 1000 V/CAT IV 600 V, 15 A – 4-mm banana plugs: CAT II 600 V, 10 A
U1162A Alligator clips	5 5	 One pair of insulated alligator clips (red and black). Recommended for use with Keysight standard test leads. CAT III 1000 V, CAT IV 600 V, 15 A
U1163A SMT grabbers		 One pair of SMT grabbers (red and black). Recommended for use with Keysight standard test leads. Rated CAT II 300 V, 3 A
U1164A Fine-tip test probes	100	 One pair of fine-tip test probes (red and black). Recommended for use with Keysight standard test leads. Rated CAT II 300 V, 3 A
U1168A Standard test lead kit		 Includes two test leads (red and black), 4-mm test probes, alligator clips, fine-tip test probes, SMT grabbers and mini grabber (black). Test leads: CAT III 1000 V, CAT IV 600 V, 15 A Test probe (19-mm tips): CAT II 1000 V, 15 A Test probe (4-mm tips): CAT III 1000 V, CAT IV 600 V, 15 A Test probe (4-mm tips): CAT III 1000 V, CAT IV 600 V, 15 A Alligator clips: CAT III 1000 V, CAT IV 600 V, 15 A Fine-tip test probes: CAT III 300 V, 3 A SMT grabber: CAT II 300 V, 3 A
U1583B AC current clamp		 Dual range: 40 A and 400 A Rated CAT III 600 V BNC-to-banana-plug adapter provided for use with DMMs -40 to 55 °C operating temperature

Ordering Information

Optional accessories

Measuring accessories (temperature) U1180A Includes thermocouple adapter, thermocouple bead J-type and Thermocouple thermocouple bead K-type. adapter+lead kit, - T/C adapter J/K-type J and K types T/C bead J-type: -20 to 200 °C - T/C bead K-type: -20 to 200 °C U1181A - Type-K T/C for use in oil and other liquids Immersion Measurement range: -50 to 700 °C - Includes adapter U1184A for connection to DMM temperature probe U1182A - Type-K T/C for use on still surfaces Industrial surface Measurement range: -50 to 400 °C Includes adapter U1184A for connection to DMM temperature probe U1183A - Type-K T/C for use in air and non-caustic gas Air temperature Measurement range: -50 to 800 °C probe - Includes adapter U1184A for connection to DMM U1184A - Mini-connector-to-banana-plug adapter for use with DMM Temperature probe adapter U1185A - T/C adapter J/K-type T/C bead J-type: -20 to 200 °C J-type thermocouple and adapter U1186A - T/C adapter J/K-type K-type T/C bead J-type: -20 to 200 °C thermocouple and adapter

Ordering Information

Optional accessories	
U1171A Magnetic hanging kit	For fastening the DMM to a steel surface so both hands are free
U1173A IR-to-USB cable	 For remote control and data logging to PC Maximum baud rate: 19,200 bits per second
U1174A Soft carrying case	The convenient way to carry your DMM and essential accessories — Dimension: 9 inches (H) x 5 inches (W) x 3 inches (D)
U1177A Bluetooth Adapter	 Enables <i>Bluetooth</i> connection to Keysight handheld digital multimeters Support the U1230, U1240, U1250 and U1270 Series handheld multimeters Remote monitoring and data logging capabilities via Android devices or Windows-based PC Recommended to use Lithium battery in lower than -20°C in temperature for long hours of operation

myKeysight

myKeysight

!X10

www.keysight.com/find/mykeysight

A personalized view into the information most relevant to you.

www.axiestandard.org

AdvancedTCA® Extensions for Instrumentation and Test (AXIe) is an open standard that extends the AdvancedTCA for general purpose and semiconductor test. Keysight is a founding member of the AXIe consortium. ATCA®, AdvancedTCA®, and the ATCA logo are registered US trademarks of the PCI Industrial Computer Manufacturers Group.

www.lxistandard.org

LAN eXtensions for Instruments puts the power of Ethernet and the Web inside your test systems. Keysight is a founding member of the LXI consortium.



www.pxisa.org

PCI eXtensions for Instrumentation (PXI) modular instrumentation delivers a rugged, PC-based high-performance measurement and automation system.



Three-Year Warranty

www.keysight.com/find/ThreeYearWarranty

Keysight's commitment to superior product quality and lower total cost of ownership. The only test and measurement company with three-year warranty standard on all instruments, worldwide.



Keysight Assurance Plans

www.keysight.com/find/AssurancePlans

Up to five years of protection and no budgetary surprises to ensure your instruments are operating to specification so you can rely on accurate measurements.



www.keysight.com/go/quality

Keysight Technologies, Inc. DEKRA Certified ISO 9001:2008 Quality Management System

Keysight Channel Partners

www.keysight.com/find/channelpartners

Get the best of both worlds: Keysight's measurement expertise and product breadth, combined with channel partner convenience.

Bluetooth and the Bluetooth logos are trademarks owned by Bluetooth SIG, Inc., U.S.A. and licensed to Keysight Technologies, Inc.

www.keysight.com/find/handheldmm

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at: www.keysight.com/find/contactus

Americas

Canada	(877) 894 4414
Brazil	55 11 3351 7010
Mexico	001 800 254 2440
United States	(800) 829 4444

Asia Pacific

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 112 929
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Other AP Countries	(65) 6375 8100

Europe & Middle East

Austria 0800 001122 Belgium 0800 58580 Finland 0800 523252 France 0805 980333 Germany 0800 6270999 Ireland 1800 832700 1 809 343051 Israel Italy 800 599100 Luxembourg +32 800 58580 Netherlands 0800 0233200 Russia 8800 5009286 Spain 0800 000154 Sweden 0200 882255 Switzerland 0800 805353 Opt. 1 (DE) Opt. 2 (FR) Opt. 3 (IT) 0800 0260637 United Kingdom

For other unlisted countries: www.keysight.com/find/contactus (BP-09-04-14)



This information is subject to change without notice. © Keysight Technologies, 2013 - 2014 Published in USA, August 3, 2014 5990-6425EN www.keysight.com

(ES) Equipements Scientifiques SA - Département Tests Energie Mesures - 127 rue de Buzenval BP 26 - 92380 Garches Tél. 01 47 95 99 45 - Fax. 01 47 01 16 22 - e-mail: tem@es-france.com - Site Web: www.es-france.com