



12.1" LED Specifications



Key Features

Sunlight Readable
LED Backlight
High Shock & Vibration Resistance
Low Power Consumption
Wide Temp. Range (-20 C~60 C)
High Uniformity (90%)
Low EMI Noise
Wide Dimming
Multiple Mounting Choices
Life Expectancy (70,000hrs)



DLF/DLH/SLO/SLD1246

Model No.	DLF1246	DLH1246	SLO1246	SLD1246
LCD Display	12.1" LED Backlight LCD			
Display Area	246.00x 184.50mm			
Brightness	1000 cd/m ²			
Resolution	800 x 600 (SVGA)			
Contrast Ratio	1000 : 1			
Pixel Pitch (mm)	0.3075(H) x 0.3075(V)			
Viewing Angle	+89 ~-89 (H), +89 ~-89 (V)			
Display Color	262K			
Response Time	25ms (Typical)			
Sync	LVDS			
Power Consumption	17W	22W	22W	22W
LED Driving Board	LI D12A01			
Control Board (Optional)		AD5621GA AD5621GD AD5766GDVA	AD5621GA AD5621GD AD5766GDVA	AD5621GA AD5621GD AD5766GDVA
F / R Control Button		5 Key 4 Key		
OSD Menu		Brightness, Contrast, H/V Position, Color, Phase, Clock....		
Dimensions (WxHxD)mm	272x204.6x13.3	272x204.6x13.3	324x254x50	338x278x59.3
Weight	752g	810g	2.3kg	3.51kg
Optional	AOT Touch Waterproof			

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Control Board (Optional)	AD5621GA/AD5621GD/AD5766GDVA
AD5621GA	VGA+Audio
AD5621GD	VGA+DVI
AD5766GDVA	VGA+CVBS+S-Video+Audio
F / R Control Button	5 Key / 4 Key (Optional)
5 Key	Power Switch, Menu, Select (+,-), Auto
4 Key	Power Switch, Menu, Select (+,-)

