



SLO 1781

17" Open Frame LCD Display, 300 nits, SXGA

SLO 1781 open frame LCD display, AOT optical bonding, touch screen capable, and customized mechanical design; fulfill the demand for extreme environments. It offers the best visibility, performance and cost effective value. The monitor brings remarkable display quality, and guaranteeing product life cycle longevity, stability, and reliability. Perfectly suitable for kiosk, ATM, POS, transportation, and outdoor industrial application.

Key Features

- High Contrast Ratio
- High Uniformity
- Fast Response Time
- Thin and Light

Applications

Transportation
Industrial



Specifications

V1

Model No.	SLO1781
Description	17" Open Frame LCD Display, 300 nits, SXGA
Display Area (mm)	337.92 x 270.336 mm
Brightness	300 cd/m ²
Resolution	1280x1024 (SXGA)
Contrast Ratio	800 : 1
Pixel Pitch (mm)	0.264(H) x 0.264(V)
Viewing Angle	170°(H), 160°(V)
Display Colors	16.7M colors
Response Time (Typical)	8ms (Typical)
Power Input	DC 12V
Power Consumption	25.8W
Dimensions (mm)	382.9x355.2x53.2
Weight (Net)	4.93kg
Control Board (Optional)	☐ AD5621GA ☐ AD5621GD ☐ AD5766GDVA ☐ AD2662GDVAR
☐ AD5621GA	VGA + Audio
☐ AD5621GD	VGA+DVI
☐ AD2662GDVAR	VGA+DVI (Optional S-Video/ Component / Audio)
F / R Control Button	☐ 5 Key ☐ 4 Key
☐ 5 Key	Power Switch, Menu, Select (+,-), Auto
☐ 4 Key	Power Switch, Menu, Select (+,-),
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock...
Optional	☐ AOT ☐ Touch Screen ☐ Waterproof

Specifications are subject to change without notice.

All brands or product names are trademarks or registered trademarks of their respective companies.

Mechanical Drawing



Unit:mm





Part Number	Description
SLO1781-SNB-A01	17",300nits,SXGA,O/B,AD5621G.12VDC,v01

Optional Accessories

Part Number	Description