


PER35A

PERFECTRON

Intel® QM77 Fanless Rugged System with Intel® Ivy Bridge Core™ i5/i3 Processor, 9V to 24V DC-in, Wide Temp. -20 to 60°C



Main Features

- Supports Intel® 22nm Ivy Bridge Processor (Mobile, rPGA988)
- 2 x DDR3 SO-DIMM up to 16 GB
- Supports 2.5" SATA HDD/SSD & CF-SATA socket
- 6 x COM ports
- 4 x USB 3.0 / 4 x USB 2.0
- Dual GbE LAN ports
- 9V ~ 24V DC-in

► Specifications

System

CPU	Intel® 22nm Ivy Bridge Processor (Mobile) socket (rPGA988) Core™ i5-3610ME 2.7 GHz (3M Cache, 35W) Core™ i3-3120ME 2.4 GHz (3M Cache, 35W)
Chipset	Intel® QM77
Memory	2 x 204-pin SO-DIMM DDR3 1333/1600 MHz up to 16 GB
Expansion Slot	1 x Mini-PCle
Storage Device	1 x 2.5" SATA HDD/SSD 1 x CFast socket

Front I/O

Power Button	Yes
Power LED	Yes
HDD LED	Yes
LPT	1
COM	5 x RS232
USB	4 x USB 2.0


Rear I/O

VGA	1
DVI-D	1
HDMI	1
Ethernet	2 x RJ45
Audio	Mic-in, Line-in, Line-out
COM	1 x RS232/422/485
USB	4 x USB 3.0
Antenna	Reserved two antenna holes
DC-Jack	1

Mechanical & Environment

Power Requirement	9V to 24V DC-in
Dimension (W x H x D)	299 x 59 x 216 mm (11.77" x 2.3" x 8.5")
Operating Temp.	-20 to 60°C (ambient with air flow)
Storage Temp.	-20 to 80°C
Relative Humidity	10% to 90%, non-condensing
Certifications	CE, FCC

► Mechanical Drawing



► Packing List

- PER35A Fanless Rugged System
- Driver CD

► Optional Accessories

Power Adapter

19V, 120W, AC/DC power adapter w/o power cord



► Ordering Information

Modules

Model Number	Description
PER35A-ET-i5-3610ME	Intel® QM77 Fanless Rugged System with Intel® Ivy Bridge Core™ i5 Processor, 9V to 24V DC-in (-20 to 60°C)
PER35A-ET-i3-3120ME	Intel® QM77 Fanless Rugged System with Intel® Ivy Bridge Core™ i3 Processor, 9V to 24V DC-in (-20 to 60°C)
PER35A-UT-i5-3610ME	Intel® QM77 Fanless Rugged System with Intel® Ivy Bridge Core™ i5 Processor, 9V to 24V DC-in (-40 to 60°C)
PER35A-UT-i3-3120ME	Intel® QM77 Fanless Rugged System with Intel® Ivy Bridge Core™ i3 Processor, 9V to 24V DC-in (-40 to 60°C)