

Datasheet

USB EDC Horizontal 2SE series

- Excelent data transfer speed
- Wear-leveling supported
- Low power consumption
- Pin pitch 2.54mm/2.00mm
- Mounting hole supported



Introduction

The Innodisk USB EDC (Embedded Disk Card) products provide high capacity USB flash memory storage that electrically complies with High-speed USB 2.0 interface & backward compatible with USB 1.1. The device features attractive small form factor and the connectivity over USB2.0 and the NAND flash architecture provide a faster data transmission.

innodisk

www.innodisk.com






(ES) Equipements Scientifiques SA - Département Modules & Systèmes Informatiques - 127 rue de Buzenval BP 26 - 92380 Garches
Tél. 01 47 95 99 80 - Fax. 01 47 01 16 22 - e-mail: msi@es-france.com - Site Web: www.es-france.com

USB EDC Horizontal 2SE series

Drawing

Contact us for more information
about the USB EDC Horizontal 2SE

Innodisk is a service-driven provider of industrial embedded flash and DRAM storage products and technologies, with a focus on the cloud computing, industrial/embedded, and aerospace and defense industries.



Specifications

Headquarters (Taiwan)

5F., No.237, Sec. 1, Datong Rd.,
Xizhi Dist., New Taipei City,
Taiwan (R.O.C.)
Tel: +886-2-77033000
Email: sales@innodisk.com

Branch Offices:

USA
usasales@innodisk.com
+1-510-770-9421
Europe
eusales@innodisk.com
+31-040-282-1818
Japan
jpsales@innodisk.com
+81-3-6667-0161
China
sales_cn@innodisk.com
+86-755-21673689
www.innodisk.com

© 2015 Innodisk Corporation.
All right reserved. Specifications
are subject to change without
prior notice.

20160422

Interface	USB 2.0
Flash Type	SLC
Connector	Standard, 9 pin, 2.54mm Low profile, 9 pin, 2.00mm
Capacity	512MB~32GB
Max. Channels	1
Sequential R/W (MB/sec, max.)	28 / 24
Max. Power Consumption	0.85 W (5V X 170mA)
H/W Write Protect	Optional
S.M.A.R.T.	-
Dimension (WxLxH)	26.6x36.9x9.6mm (Pin Pitch2.54) 26.6x36.9x6.6mm (Pin Pitch2.00)
Environment	Vibration: 5G @7~2000Hz Shock: 50G @ 0.5ms Storage Temperature: -55°C ~ +95°C MTBF: 3 million hours

Ordering Information

Pin Pitch	2.54mm						
Operation Temp.	512MB	1GB	2GB	4GB	8GB	16GB	32GB
Standard Grade (0°C ~ +70°C)	DEUH1-512I72AC1SB	DEUH1-01GI72AC1SB	DEUH1-02GI72AC1SB	DEUH1-04GI72AC1SB	DEUH1-08GI72AC1SB	DEUH1-16GI72AC1SB	DEUH1-32GI72AC1SB
Industrial Grade (-40°C ~ +85°C)	DEUH1-512I72AW1SB	DEUH1-01GI72AW1SB	DEUH1-02GI72AW1SB	DEUH1-04GI72AW1SB	DEUH1-08GI72AW1SB	DEUH1-16GI72AW1SB	DEUH1-32GI72AW1SB
Pin Pitch	2.00mm						
Operation Temp.	512MB	1GB	2GB	4GB	8GB	16GB	32GB
Standard Grade (0°C ~ +70°C)	DEUH2-512I72AC1SB	DEUH2-01GI72AC1SB	DEUH2-02GI72AC1SB	DEUH2-04GI72AC1SB	DEUH2-08GI72AC1SB	DEUH2-16GI72AC1SB	DEUH2-32GI72AC1SB
Industrial Grade (-40°C ~ +85°C)	DEUH2-512I72AW1SB	DEUH2-01GI72AW1SB	DEUH2-02GI72AW1SB	DEUH2-04GI72AW1SB	DEUH2-08GI72AW1SB	DEUH2-16GI72AW1SB	DEUH2-32GI72AW1SB

innodisk

www.innodisk.com

(ES) Equipements Scientifiques SA - Département Modules & Systèmes Informatiques - 127 rue de Buzenval BP 26 - 92380 Garches
Tél. 01 47 95 99 80 - Fax. 01 47 01 16 22 - e-mail: msi@es-france.com - Site Web: www.es-france.com