

DATASHEET

Module TYPE	DDR3 16GB/8GB/4GB/2GB/1GB SODIMM
Module speed	PC3-12800
CAS Latency	CL-11
Pin	204pin
SDRAM Operating Temp	0 °C ~ 85 °C

1. Features

Key Parameter

Industry Nomenclature	Speed Grade	Data Rate MT/s			tRCD	tRP	tRC
		CL=7	CL=9	CL=11	(ns)	(ns)	(ns)
PC3-12800	-	1066	1333	1600	13.125	13.125	13.125

JEDEC Standard 204-pin Dual In-Line Memory Module

- Intend for PC3-12800 applications

- Inputs and Outputs are SSTL-15 compatible

- VDD=VDDQ= 1.5 Volt $\pm$ 0.075

- VDD=VDDQ= 1.35 Volt (-0.067/+0.1V)

- Bi-directional Differential Data Strobe

- DLL aligns DQ and DQS transition with CK transition

- SDRAMs have 8 internal banks for concurrent operation

- Normal and Dynamic On-Die Termination support.

- SDRAMs are 78-ball BGA Package

- 8 bit pre-fetch

- Two different termination values (Rtt_Nom & Rtt_WR)

- Auto & self refresh 7.8 μ s ($T_A \leq +85^{\circ}\text{C}$)

- DRAM operating temperature range

$0^{\circ}\text{C} \leq T_A \leq +85^{\circ}\text{C}$

- Programmable Device Operation:

- Burst Type: Sequential or Interleave


- Device CAS# Latency: 9

- Burst Length: switch on-the-fly:

BL=8 or BC 4

- RoHS Compliant (Section 14)

2. PACKAGE DIMENSION



Note: Device position is only for reference.

3. Ordering Information

Type & Speed	Density	Height	Innodisk Memory P/N
DDR3L-1600 SODIMM	16GB	1.18"	M3S0-AGM1DLPC
	8GB	1.18"	M3S0-8GSSDLPC
	4GB	1.18"	M3S0-4GSSCLPC
	2GB	1.18"	M3S0-2GSJCLPC
	1GB	1.18"	M3S0-1GPFCLPC