# **PROFITAP**

### **ProfiShark 1G**

## **All-in-One Gigabit Ethernet Troubleshooter**

The Ultimate Solution for Field Testing & Monitoring

A full featured field service tool, compact and easy to use.

All-in-one in a pocket-sized box, the only additional hardware required being a PC with a free USB 3.0 port, the ProfiShark 1G is the perfect tool for the field engineer as well as for long-term traffic collection. As it is based on USB 3.0 (5 Gbit/s), the ProfiShark 1G manages full-duplex Gigabit at wirespeed.

#### **Features**

- 10/100/1G monitoring on USB 3.0
- USB 3.0 powered
- Fail-safe monitoring
- Hardware aggregation
- SPAN and In-Line modes
- 8 ns hardware timestamp
- Real time statistics
- · Low level error and bandwidth monitoring
- Direct capture to disk
- · Invisible to the network
- PoE compliant

#### The ProfiShark 1G has the ability to capture:

Any frames between 10 bytes and 10 Kbytes

Any encapsulated frames


• Any type of frames (VLAN, VXLAN, MPLS, Pause, CRC error frames...)

#### **Timestamp**

This feature allows real time analysis of aggregated and buffered traffic. It can measure latencies in nanosecond resolution.

#### **ProfiShark Manager**

An application designed specifically for the ProfiShark 1G. It provides a way for statistical analysis of a network, allowing for efficient excessive bandwidth usage detection, or any low layer errors using charts prior to a deeper investigation with an analyzer.



5Gb/s USB3.0 **SMALLER I IGHTFR FASTFR** 

1000

10 100

Network **USB 3.0** 

Link/Activity

**Power LED** 

**FRONT** 

**BACK** 

Connectors 2 x RJ45 8 pins • 1 x USB 3.0 / USB 2.0 • 1 x 5 VDC optional input

LEDs 2 x Link activity • 2 x Speed • 1 x Power

Max. Network Latency Link @ 1 Gbps 370 ns • Link @ 100 Mbps 660 ns • Link @ 10 Mbps 6600 ns

System requirements Dual Core Processor • 4 GB memory • USB 3.0 port

Supported OS Windows 10 • Windows 8 32-bit & 64-bit • Windows 7 32-bit & 64-bit • Linux

Dimensions (WxDxH) 69 x 124 x 24 mm • 2.72 x 4.88 x 0.94 in

Weight 176 g • 0.39 lb

Accessories 1.8 m USB 3.0 cable • RJ45 cable • Pouch • USB key

Profitap HQ B.V. High Tech Campus 9 5656 AE Eindhoven The Netherlands +31 (0) 40 782 0880 www.profitap.com

Connection

Link/Activity

Optional DC input 5V/1A