

DIVIDUAL ETI



THE **DIVIDUAL ETI** IS A REAL-TIME ETI STREAM RECORDER AND PLAYER IN A POCKET-SIZED AND ROBUST DEVICE.

CHARACTERISTICS

1x ASI input and 1x ASI output for DAB/DAB+/T-DMB
ETI NI (G703) supported
ETI NA5592 & NA5376 (G704) supported
Playlist/segment/loop play mode
Scheduled recording
Player/Recorder command line software
Compatible MS Windows XP/Vista/7
USB self-powered, 140 g

TECHNICAL CHARACTERISTICS

DVB-ASI	
Connector In	1 x BNC female - 75 Ω
Connector Out	1 x BNC female - 75 Ω
Max bitrate	2048 Kbps
USB Data connector	1 x USB2 B-Type
Power supply	USB self-powered
Environment	
Operating temperature	-20 to +55 °C / -4 to 131 °F
Physical	
Dimensions	115 x 62 x 27 mm / 4.5 x 2.4 x 1 in
Weight	140 g

STREAM RECORDING/PLAYING


Standard and scheduled recording
Loop/segment play modes
Stream playlist handling

ORDERING CODE

DiviDual ETI

DAB, DAB+, T-DMB Recorder, Player
Shipped bundled with DiviSuite ETI software for MS Windows XP/Vista/7

48HMAX SHIPMENT



➤ TO TEST APPLICATIONS

➤ TO ACHIEVE COST-EFFICIENCY ON BROADCAST NETWORKS



APPLICATIONS

- R&D Streams Analysis and Generation
- Installation & Maintenance Test Tool
- Portable Demonstration Setup

KEY BENEFITS

- 2-in-1 product: Baseband Recorder + Player
- Compact (pocket size, 140 g) and USB self-powered
- Command line package for automated testing
- **ETI-G703/G704 support**
- Configurable play and record modes

