

# L1985-EN25L0-RT

## Specification

19" LCD monitor, 1280 x 1024, LED 250 nits, VGA input



### Features

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Available with auto-brightness sensor offers application in day and night
- VGA connector with optional AV,SV,AV-Looping
- Complete custom design/solution for OEM customers

|                     |                                                                                          |                                                             |                                                         |
|---------------------|------------------------------------------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------|
| Panel               | Cell Type / Glass Surface                                                                | TFT LCD / Black Anti-Glare, low reflection coating          |                                                         |
|                     | Aspect Ratio / Size                                                                      | 5 : 4 / 19" viewable diagonal area                          |                                                         |
|                     | Active Area / Pixel Pitch                                                                | 376.3(H) x 301.1(V) mm / 0.294(H) x 0.294(V) mm             |                                                         |
|                     | Native Resolution / Colors                                                               | 1280(H) x 1024(V) / 16.7 M                                  |                                                         |
|                     | Brightness / Contrast                                                                    | 250 cd/m <sup>2</sup> (typ) / 800 : 1                       |                                                         |
|                     | Response Time                                                                            | ≤ 5 ms                                                      |                                                         |
|                     | Viewing Angle (typical)                                                                  | H. 170° (- 85° ~ + 85°) , V. 160°(- 80° ~ + 80°)            |                                                         |
|                     | Light Source                                                                             | LED backlight, Long life, 35,000 hrs (typ)                  |                                                         |
| Input Sources       | PC System                                                                                | Signal                                                      | Analog RGB (0.7/1.0 V <sub>p-p</sub> , 75 ohms)         |
|                     |                                                                                          | Sync                                                        | Separate Sync, Composite Sync, Sync On Green            |
|                     |                                                                                          | Frequency                                                   | F <sub>h</sub> : 30 - 82Khz , F <sub>v</sub> : 50 -75Hz |
|                     | Audio System                                                                             | 2W speaker x 2                                              |                                                         |
| Input Terminals     | 1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug |                                                             |                                                         |
| Convenient Features | Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)               |                                                             |                                                         |
|                     | OSD Multi-Languages , Wall Mount Ready (VESA Dimension - please refer to Drawing)        |                                                             |                                                         |
| Power               | 12VDC-IN with external power adapter                                                     |                                                             |                                                         |
| Power Consumption   | Operation / Power Saving                                                                 | 32.5 watt , < 2 watt (Support DPMS)                         |                                                         |
| Operating Condition | Temperature / Humidity                                                                   | 0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)     |                                                         |
| Storage Condition   | Temperature / Humidity                                                                   | - 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation) |                                                         |
| Certification       |                                                                                          | FCC , CE                                                    |                                                         |
| Dimensions          | Physical                                                                                 | Please refer to Drawing                                     |                                                         |
|                     | Carton                                                                                   | W x H x D = TBD                                             |                                                         |
| Weight              | N.W. / G.W.                                                                              | 6 Kgs / 7 Kgs                                               |                                                         |
| Container Loaded    | 20ft / 40ft / 40ft HQ                                                                    | TBD (Sets , By pallet)                                      |                                                         |

|                            |                |                                                             |
|----------------------------|----------------|-------------------------------------------------------------|
| 5 Wires<br>Resistive Touch | Resolution     | 2048 x 2048                                                 |
|                            | Touch Method   | Finger, gloved hand or any other pointer                    |
|                            | Touch Accuracy | ± 2mm (for 42" screen) over 90% of the touch sensitive area |

| Options | Touch            | Video / TV           | Enhanced Panel           | Others                       |
|---------|------------------|----------------------|--------------------------|------------------------------|
|         | Resistive touch  | SV + AV              | Panel with LED backlight | Digital Signage(Stand alone) |
|         | Capacitive touch | SV + AV + AV_Looping | High brightness panel    | Networking Digital Signage   |
|         | SAW touch        | SV + AV + TV         | Wide Temperature         | Motion Sensor                |
|         | Infrared touch   |                      | Sunlight Readable        | Light Sensor                 |
|         | Protected glass  |                      |                          | Auto-Dimming                 |

**Winsonic®**  
Winsonic Electronics Co., Ltd.

# L1985-EN25L2-RT

## Specification

19" LCD monitor, 1280 x 1024, LED 250 nits, VGA input, wide view angle



### Features

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Available with auto-brightness sensor offers application in day and night
- VGA connector with optional AV,SV,AV-Looping
- Complete custom design/solution for OEM customers

|                     |                                                                                          |                                                             |                                                         |
|---------------------|------------------------------------------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------|
| Panel               | Cell Type / Glass Surface                                                                | TFT LCD / Black Anti-Glare, low reflection coating          |                                                         |
|                     | Aspect Ratio / Size                                                                      | 5 : 4 / 19" viewable diagonal area                          |                                                         |
|                     | Active Area / Pixel Pitch                                                                | 376.3(H) x 301.1(V) mm / 0.294(H) x 0.294(V) mm             |                                                         |
|                     | Native Resolution / Colors                                                               | 1280(H) x 1024(V) / 16.7 M                                  |                                                         |
|                     | Brightness / Contrast                                                                    | 250 cd/m <sup>2</sup> (typ) / 1000 : 1                      |                                                         |
|                     | Response Time                                                                            | ≤ 5 ms                                                      |                                                         |
|                     | Viewing Angle (typical)                                                                  | H. 178° (- 89° ~ + 89°) , V. 178°(- 89° ~ + 89°)            |                                                         |
|                     | Light Source                                                                             | LED backlight, Long life, 35,000 hrs (typ)                  |                                                         |
| Input Sources       | PC System                                                                                | Signal                                                      | Analog RGB (0.7/1.0 V <sub>p-p</sub> , 75 ohms)         |
|                     |                                                                                          | Sync                                                        | Separate Sync, Composite Sync, Sync On Green            |
|                     |                                                                                          | Frequency                                                   | F <sub>h</sub> : 30 - 82Khz , F <sub>v</sub> : 50 -75Hz |
|                     | Audio System                                                                             | 2W speaker x 2                                              |                                                         |
| Input Terminals     | 1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug |                                                             |                                                         |
| Convenient Features | Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)               |                                                             |                                                         |
|                     | OSD Multi-Languages , Wall Mount Ready (VESA Dimension - please refer to Drawing)        |                                                             |                                                         |
| Power               | 12VDC-IN with external power adapter                                                     |                                                             |                                                         |
| Power Consumption   | Operation / Power Saving                                                                 | 32.5 watt , < 2 watt (Support DPMS)                         |                                                         |
| Operating Condition | Temperature / Humidity                                                                   | 0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)     |                                                         |
| Storage Condition   | Temperature / Humidity                                                                   | - 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation) |                                                         |
| Certification       |                                                                                          | FCC , CE                                                    |                                                         |
| Dimensions          | Physical                                                                                 | Please refer to Drawing                                     |                                                         |
|                     | Carton                                                                                   | W x H x D = TBD                                             |                                                         |
| Weight              | N.W. / G.W.                                                                              | 6 Kgs / 7 Kgs                                               |                                                         |
| Container Loaded    | 20ft / 40ft / 40ft HQ                                                                    | TBD (Sets , By pallet)                                      |                                                         |

|                            |                |                                                             |
|----------------------------|----------------|-------------------------------------------------------------|
| 5 Wires<br>Resistive Touch | Resolution     | 2048 x 2048                                                 |
|                            | Touch Method   | Finger, gloved hand or any other pointer                    |
|                            | Touch Accuracy | ± 2mm (for 42" screen) over 90% of the touch sensitive area |

| Options | Touch            | Video / TV           | Enhanced Panel           | Others                       |
|---------|------------------|----------------------|--------------------------|------------------------------|
|         | Resistive touch  | SV + AV              | Panel with LED backlight | Digital Signage(Stand alone) |
|         | Capacitive touch | SV + AV + AV_Looping | High brightness panel    | Networking Digital Signage   |
|         | SAW touch        | SV + AV + TV         | Wide Temperature         | Motion Sensor                |
|         | Infrared touch   |                      | Sunlight Readable        | Light Sensor                 |
|         | Protected glass  |                      |                          | Auto-Dimming                 |

**Winsonic®**  
Winsonic Electronics Co., Ltd.

# L1985-ENA0L0-RT

## Specification

19" LCD monitor, 1280 x 1024, LED 1000 nits, VGA input



### Features

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Available with auto-brightness sensor offers application in day and night
- VGA connector with optional AV,SV,AV-Looping
- Complete custom design/solution for OEM customers

|                     |                                                                                          |                                                             |                                                         |
|---------------------|------------------------------------------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------|
| Panel               | Cell Type / Glass Surface                                                                | TFT LCD / Black Anti-Glare, low reflection coating          |                                                         |
|                     | Aspect Ratio / Size                                                                      | 5 : 4 / 19" viewable diagonal area                          |                                                         |
|                     | Active Area / Pixel Pitch                                                                | 376.3(H) x 301.1(V) mm / 0.294(H) x 0.294(V) mm             |                                                         |
|                     | Native Resolution / Colors                                                               | 1280(H) x 1024(V) / 16.7 M                                  |                                                         |
|                     | Brightness / Contrast                                                                    | 1000 cd/m <sup>2</sup> (typ) / 800 : 1                      |                                                         |
|                     | Response Time                                                                            | ≤ 5 ms                                                      |                                                         |
|                     | Viewing Angle (typical)                                                                  | H. 170° (- 85° ~ + 85°) , V. 160°(- 80° ~ + 80°)            |                                                         |
|                     | Light Source                                                                             | LED backlight, Long life, 35,000 hrs (typ)                  |                                                         |
| Input Sources       | PC System                                                                                | Signal                                                      | Analog RGB (0.7/1.0 V <sub>p-p</sub> , 75 ohms)         |
|                     |                                                                                          | Sync                                                        | Separate Sync, Composite Sync, Sync On Green            |
|                     |                                                                                          | Frequency                                                   | F <sub>h</sub> : 30 - 82Khz , F <sub>v</sub> : 50 -75Hz |
|                     | Audio System                                                                             | 2W speaker x 2                                              |                                                         |
| Input Terminals     | 1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug |                                                             |                                                         |
| Convenient Features | Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)               |                                                             |                                                         |
|                     | OSD Multi-Languages , Wall Mount Ready (VESA Dimension - please refer to Drawing)        |                                                             |                                                         |
| Power               | 12VDC-IN with external power adapter                                                     |                                                             |                                                         |
| Power Consumption   | Operation / Power Saving                                                                 | 33 watt , < 2 watt (Support DPMS)                           |                                                         |
| Operating Condition | Temperature / Humidity                                                                   | 0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)     |                                                         |
| Storage Condition   | Temperature / Humidity                                                                   | - 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation) |                                                         |
| Certification       |                                                                                          | FCC , CE                                                    |                                                         |
| Dimensions          | Physical                                                                                 | Please refer to Drawing                                     |                                                         |
|                     | Carton                                                                                   | W x H x D = TBD                                             |                                                         |
| Weight              | N.W. / G.W.                                                                              | 6 Kgs / 7 Kgs                                               |                                                         |
| Container Loaded    | 20ft / 40ft / 40ft HQ                                                                    | TBD (Sets , By pallet)                                      |                                                         |

|                            |                |                                                             |
|----------------------------|----------------|-------------------------------------------------------------|
| 5 Wires<br>Resistive Touch | Resolution     | 2048 x 2048                                                 |
|                            | Touch Method   | Finger, gloved hand or any other pointer                    |
|                            | Touch Accuracy | ± 2mm (for 42" screen) over 90% of the touch sensitive area |

| Options | Touch            | Video / TV           | Enhanced Panel           | Others                       |
|---------|------------------|----------------------|--------------------------|------------------------------|
|         | Resistive touch  | SV + AV              | Panel with LED backlight | Digital Signage(Stand alone) |
|         | Capacitive touch | SV + AV + AV_Looping | High brightness panel    | Networking Digital Signage   |
|         | SAW touch        | SV + AV + TV         | Wide Temperature         | Motion Sensor                |
|         | Infrared touch   |                      | Sunlight Readable        | Light Sensor                 |
|         | Protected glass  |                      |                          | Auto-Dimming                 |

**Winsonic®**  
Winsonic Electronics Co., Ltd.

# L1985-ENA0L2-RT

## Specification

19" LCD monitor, 1280 x 1024, LED 1000 nits, VGA input, wide view angle



### Features

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Available with auto-brightness sensor offers application in day and night
- VGA connector with optional AV,SV,AV-Looping
- Complete custom design/solution for OEM customers

|                     |                                                                                          |                                                             |                                                         |
|---------------------|------------------------------------------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------|
| Panel               | Cell Type / Glass Surface                                                                | TFT LCD / Black Anti-Glare, low reflection coating          |                                                         |
|                     | Aspect Ratio / Size                                                                      | 5 : 4 / 19" viewable diagonal area                          |                                                         |
|                     | Active Area / Pixel Pitch                                                                | 376.3(H) x 301.1(V) mm / 0.294(H) x 0.294(V) mm             |                                                         |
|                     | Native Resolution / Colors                                                               | 1280(H) x 1024(V) / 16.7 M                                  |                                                         |
|                     | Brightness / Contrast                                                                    | 1000 cd/m <sup>2</sup> (typ) / 1000 : 1                     |                                                         |
|                     | Response Time                                                                            | ≤ 5 ms                                                      |                                                         |
|                     | Viewing Angle (typical)                                                                  | H. 178° (- 89° ~ + 89°) , V. 178°(- 89° ~ + 89°)            |                                                         |
|                     | Light Source                                                                             | LED backlight, Long life, 35,000 hrs (typ)                  |                                                         |
| Input Sources       | PC System                                                                                | Signal                                                      | Analog RGB (0.7/1.0 V <sub>p-p</sub> , 75 ohms)         |
|                     |                                                                                          | Sync                                                        | Separate Sync, Composite Sync, Sync On Green            |
|                     |                                                                                          | Frequency                                                   | F <sub>h</sub> : 30 - 82Khz , F <sub>v</sub> : 50 -75Hz |
|                     | Audio System                                                                             | 2W speaker x 2                                              |                                                         |
| Input Terminals     | 1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug |                                                             |                                                         |
| Convenient Features | Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)               |                                                             |                                                         |
|                     | OSD Multi-Languages , Wall Mount Ready (VESA Dimension - please refer to Drawing)        |                                                             |                                                         |
| Power               | 12VDC-IN with external power adapter                                                     |                                                             |                                                         |
| Power Consumption   | Operation / Power Saving                                                                 | 33 watt , < 2 watt (Support DPMS)                           |                                                         |
| Operating Condition | Temperature / Humidity                                                                   | 0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)     |                                                         |
| Storage Condition   | Temperature / Humidity                                                                   | - 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation) |                                                         |
| Certification       |                                                                                          | FCC , CE                                                    |                                                         |
| Dimensions          | Physical                                                                                 | Please refer to Drawing                                     |                                                         |
|                     | Carton                                                                                   | W x H x D = TBD                                             |                                                         |
| Weight              | N.W. / G.W.                                                                              | 6 Kgs / 7 Kgs                                               |                                                         |
| Container Loaded    | 20ft / 40ft / 40ft HQ                                                                    | TBD (Sets , By pallet)                                      |                                                         |

|                            |                |                                                             |
|----------------------------|----------------|-------------------------------------------------------------|
| 5 Wires<br>Resistive Touch | Resolution     | 2048 x 2048                                                 |
|                            | Touch Method   | Finger, gloved hand or any other pointer                    |
|                            | Touch Accuracy | ± 2mm (for 42" screen) over 90% of the touch sensitive area |

|         |                  |                      |                          |                              |
|---------|------------------|----------------------|--------------------------|------------------------------|
| Options | Touch            | Video / TV           | Enhanced Panel           | Others                       |
|         | Resistive touch  | SV + AV              | Panel with LED backlight | Digital Signage(Stand alone) |
|         | Capacitive touch | SV + AV + AV_Looping | High brightness panel    | Networking Digital Signage   |
|         | SAW touch        | SV + AV + TV         | Wide Temperature         | Motion Sensor                |
|         | Infrared touch   |                      | Sunlight Readable        | Light Sensor                 |
|         | Protected glass  |                      |                          | Auto-Dimming                 |

**Winsonic®**  
Winsonic Electronics Co., Ltd.