

DWF4602-31P-70

Specification

46" Display Wall Frame, 3x1 Portrait, 700nits, super narrow bezel



Features

- 2.5 mm super Narrow Bezel Display Wall Frame.
- Fit with Winsonic Display Wall Monitor x 3 pcs
- Easy Mounting solution
- Cable Management solution

Spec of Frame

Monitor Arrangement	3 x 1 Portrait	
Resolution	3240 x 1920	
Dimension	Physical	1737.41 x 1023.68 x 207 (mm)
	Carton	TBD
	N.W. / G.W.	TBD

Spec of LCD Monitor (for single unit)

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	Wide / 46" viewable diagonal area	
	Active Area / Pixel Pitch	1018.08(H) x 572.67(V) mm / 0.176(H) x 0.53(V) mm	
	Native Resolution / Colors	1920(H) x 1080(V) / 1073.7 Million	
	Brightness / Contrast	700 cd/m ² (typ) / 4000 : 1	
	Response Time	≤ 6.5 ms (G-to-G)	
	Viewing Angle (typical)	H. 178° (- 89° ~ + 89°) , V. 178° (- 89° ~ + 89°)	
	Light Source	LED, Long life, 50,000 hrs (typ)	
Input Sources	PC System	Signal	Analog RGB (0.7/1.0 V _{p-p} , 75 ohms)
			Digital (DVI-D)
		Sync	Separate Sync, Composite Sync, Sync On Green
		Frequency	F _H : 30 - 82Khz , F _V : 50 -75Hz
Input Terminals	1 x VGA (15 Pin Female D-Sub) , 1 x DVI, 1 x AC Inlet		
Convenient Features	Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)		
	OSD Multi-Languages		
Power	Internal power supply with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz		
Power Consumption	Operation / Power Saving	275 watt , < 5 watt (Support DPMS)	
Operating Condition	Temperature / Humidity	0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)	
Storage Condition	Temperature / Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation)	
Certification		FCC , CE	
Dimensions	Physical	W x H x D : 578.27 x 1023.68 x 139.5 (mm)	
	Carton	W x H x D = TBD	
Weight	N.W. / G.W.	25.0 Kgs / 27.5 Kgs	

Winsonic®

Winsonic Electronics Co., Ltd.