

WPF6 Probe

100 kHz - 6 GHz




- High sensitivity from 0.2 V/m
- Isotropic & True RMS measurement
- Excellent attenuation at 50/60 Hz
- Measurements in accordance with International Standards

100 kHz - 6 GHz

E

RMS

ISOTROPIC



Telecommunications
Certification and audit of telecommunication services (GSM, 3G, LTE, TDT, FM, WiFi, etc.).



Industry
Assessment of industrial processes for worker's exposure protection



Radar/Aerospace
Assessment of radar and aerospace sites and personnel exposure protection.



Labs/R&D
RF exposure protection of R&D and labs personnel.



Technical Specifications

	WPF6	WPF6-HP High Power version
Part Number	WWP0601	WWP0602
Frequency range	100 kHz – 6 GHz	
Sensor type	Isotropic RMS diode technology	
Type of frequency response	Flat	
Measurement range	0.2 – 130 V/m (CW) 0.2 – 20 V/m (True RMS)	0.2 – 1000 V/m (CW) 0.2 – 20 V/m (True RMS)
Dynamic range	56 dB	73 dB
Sensitivity	0.2 V/m	
Resolution	0.02 V/m (until 7.5 V/m) 0.1 V/m (from 7.5 V/m to 130 V/m)	
Frequency response (*)	Better than -3 dB @ 100 kHz ± 1.5 dB (250 kHz – 5.5 GHz) Better than -2 dB (5.5 – 6 GHz)	
Linearity	± 0.5 dB (0.5 V/m – 100 V/m)	
Isotropic deviation	± 0.3 dB (1 GHz) ± 1 dB (6 GHz)	
Calibration	ISO 17025 Accredited Calibration (ILAC)	
Calibration period	24 months (recommended)	
Temperature range	- 20 °C to 50 °C	
Temperature response	+ 0.1 / - 1 dB (related to 20 °C)	
Dimensions	28.4 cm x 6 cm Ø	
Weight	95 g	
Attenuation at 50/60 Hz	> 80 dB	

(*) The frequency response can be corrected with the SMP3/SMP2 by using the correction factors stored in the probe (ISO 17025 accredited calibration).



WPF6_EN_2601_v2.6

Compatible with **SMP3**, **SMP2**, **MonitEM**, **MapEM**



ES France - Département Tests & Mesures
127 rue de Buzenval BP 26 - 92380 Garches



Tél. 01 47 95 99 45



e-mail : tem@es-france.com
Site Web : www.es-france.com