

# WPH1000 Field Probe

## 30 MHz - 1000 MHz




- High sensitivity from 0.018 A/m
- Isotropic and RMS measurement
- Measurements in accordance with International Standards

30 MHz - 1000 MHz

H

RMS

ISOTROPIC



**Telecommunications:** certification and audit of telecommunication services.



**Industry:** assessment of industrial processes for workers' exposure protection.



**Defence:** assessment of military sites and personnel exposure protection.



**Labs/R&D:** RF exposure protection of R&D and labs personnel.

## Technical Specifications

Frequency range	30 MHz - 1000 MHz
Sensor type	Isotropic, RMS Diode Technology
Type of frequency response	Flat
Measurement range	0.018 - 20 A/m
Damage Level CW	35 A/m (350 A/m Peak 1 $\mu$ s, period 100 $\mu$ s)
Dynamic range	60 dB
Sensitivity	0.018 A/m
Frequency response (*)	$\pm 0.5$ dB (30 MHz - 400 MHz) $\pm 1$ dB (30 MHz - 1000 MHz) > -3 dB @ 25 MHz
Linearity	$\pm 1$ dB (0.04 to 4 A/m)
Axial isotropy	$\pm 1$ dB
Calibration period	24 months (recommended)
Temperature range	- 10 °C to 50 °C
Dimensions	28.4 cm x 6 cm $\varnothing$
Weight	95 g

(\*) The frequency response can be corrected with the SMP2 by using the correction factors stored in the probe.

Compatible with **SMP2**, Monit**EM**

Product specifications and descriptions in this document subject to change without notice



WPH1000\_EN\_1705\_v1.1