

Digital Hand-held "Pocket" Meter for Corrosion Inhibitor Solutions PAL-AntiRust



The high resolution of 0.01% makes the PAL-AntiRust ideal for measuring low-concentration solutions, such as corrosion inhibitor fluids.

Specifications

Model	PAL-AntiRust
Cat.No.	4537
Scale	AntiRust Temperature
Measurement Range	AntiRust : 0.00 to 25.00% Temperature : 10.0 to 100° C
Resolution	AntiRust : 0.01% Temperature : 0.1° C
Measurement Accuracy	AntiRust : $\pm 0.10\%$ Temperature : $\pm 1^{\circ}$ C
Temperature compensation range	10 to 100° C (Automatic Temperature Compensation)
Ambient Temperature	10 to 40° C
Sample Volume	At least 0.3mL
Measurement Time	Approx. 5 seconds 30 seconds of continuous measurement
Power Supply	2 x AAA Batteries
Battery Life	Approx. 11,000 times measurement (when alkaline batteries are used)
International Protection Class	IP65 Dust-tight and Protected against water jets.
Dimensions & Weight	55(W) x 31(D) x 109(H)mm, 100g (Main Unit only)

Options

- [PAL-CASE](#) : RE-39409
- [PAL Silicone Cover](#) : RE-39413
- [STRAP](#) : RE-39410