


- Reed Relay Matrix Module
- 12x4, Dual 12x4, 24x4 or 12x8
- 1-Pole, 2-Pole or Screened Versions
- Large Matrices Built Using Multiple Modules
- Screened 50Ω Option with 50MHz Bandwidth
- Uses High Reliability Pickering Reed Relays For Maximum Performance
- Fast Operating Speed < 500μs
- Switch up to 150Volts, 1.2A with 20W Max Power
- VISA, IVI & Kernel Drivers Supplied for Windows
- Supported by PXI or LXI Chassis
- Supported by *eBIRST*™
- 3 Year Warranty




The 40-510 series of reed relay based matrix modules feature a wide range of selectable switching configurations (12x4, dual 12x4, 12x8 and 24x4). Typical applications include signal routing in ATE and data acquisition systems.


Available formats are 1-pole, 2-pole and 1-Pole screened. The screened version is suitable for switching signals up to 50MHz. Larger matrices may be constructed by daisy chaining the common signals from multiple PXI modules.

Supported by *eBIRST*


eBIRST switching system test tools simplify switching system fault-finding by quickly testing the system and graphically identifying the faulty relay.




40-510 Matrix 12x4



40-512 Matrix 12x8 2-pole
(each line is a 2 wire connection)



40-511 Matrix Dual 12x4



40-513 Matrix 24x4

Relay Type

The 40-510 series of modules are fitted with ruthenium sputtered reed relays, these offer very long life with good low level switching performance and excellent contact resistance stability. Spare reed relays are fitted onto the circuit board to allow easy maintenance with minimum downtime.

Switching Specification

Switch Type:	Ruthenium Reed
Max Switch Voltage:	150VDC/100VAC*
Max Power:	20W
Max Switch Current:	1A
Max Carry Current:	1.2A
Initial Path Resistance	
On (single module):	<600mΩ (40-510/511) <1000mΩ (40-512) <800mΩ (40-513)
Off (single module):	>10 ⁹ Ω
Differential Thermal Offset:	<15μV
Operate Time:	<0.5ms, 0.25ms typical
Release Time:	<0.5ms, 0.25ms typical
Expected Life, low power load:	1x10 ⁹ operations
Expected Life, full power load:	>5x10 ⁶ operations

* For full voltage rating, signal sources to be switched must be fully isolated from mains supply and safety earth.

Isolation and Crosstalk (screened reed versions)

Crosstalk	
@1MHz:	62dB (typical)
@10MHz:	42dB (typical)
@25MHz:	40dB (typical)
Isolation	
@1MHz:	65dB (typical)
@10MHz:	49dB (typical)
@25MHz:	45dB (typical)

Power Requirements

+3.3V	+5V	+12V	-12V
0	400mA (typ 280mA)	0	0

Mechanical Characteristics

Single slot 3U PXI (CompactPCI card).

Module weight: 280g (40-513-021).
260g (40-513-022).

3D models for all versions in a variety of popular file formats are available on request.

Connectors

PXI bus via 32-bit P1/J1 backplane connector.

Signals via front panel 68-pin female micro-D connector, for pin outs please refer to the operating manual.

Operating/Storage Conditions

Operating Conditions

Operating Temperature: 0°C to +55°C
Humidity: Up to 90% non-condensing
Altitude: 5000m

Storage and Transport Conditions

Storage Temperature: -20°C to +75°C
Humidity: Up to 90% non-condensing
Altitude: 15000m


PXI & CompactPCI Compliance

The module is compliant with the PXI Specification 2.2. Local Bus, Trigger Bus and Star Trigger are not implemented.

Uses a 33MHz 32-bit backplane interface.

Safety & CE Compliance

All modules are fully CE compliant and meet applicable EU directives: Low-voltage safety EN61010-1:2010, EMC Immunity EN61326-1:2013, Emissions EN55011:2009+A1:2010.



PCB Layout for the 40-510 Matrix Module

Product Order Codes

Single 12x4 Matrix, 1-Pole	40-510-021
Single 12x4 Matrix, 2-Pole	40-510-022
Dual 12x4 Matrix, 1-Pole	40-511-021
Dual 12x4 Matrix, 2-Pole	40-511-022
Single 12x8 Matrix, 1-Pole	40-512-021
Single 12x8 Matrix, 2-Pole	40-512-022
Single 24x4 Matrix, 1-Pole	40-513-021
Single 24x4 Matrix, 2-Pole	40-513-022

Options:

-S All 1 pole versions are available with screened reed relays (e.g. 40-512-021-S)

Product Customization

Pickering PXI modules are designed and manufactured on our own flexible manufacturing lines, giving complete product control and enabling simple customization to meet very specific requirements.

Customization can include:

- Alternative reed relay types
- Mixture of reed relay types
- Alternative number of relays
- Different performance specifications

All customized products are given a unique part number, fully documented and may be ordered at any time in the future. Please contact your local sales office to discuss.

Support Products

eBIRST Switching System Test Tool

This product is supported by the eBIRST test tools which simplify the identification of failed relays, the required eBIRST tools are below.

Product	Test Tool	Adaptor
All Types	93-006-001	93-006-401

Spare Relay Kits

Kits of replacement relays are available for the majority of Pickering's PXI switching products, simplifying servicing and reducing down-time.

Product	Relay Kit
40-510-021	91-100-003
40-510-021-S	91-100-011
40-510-022	91-100-008
40-511-021	91-100-003
40-511-021-S	91-100-011
40-511-022	91-100-008
40-512-021	91-100-003
40-512-021-S	91-100-011
40-512-022	91-100-008
40-513-021	91-100-003
40-513-021-S	91-100-011
40-513-022	91-100-008

For further assistance, please contact your local Pickering sales office.

Mating Connectors & Cabling

For connection accessories for the 40-510 series please refer to the [90-015D](#) 68-pin micro-D Connector Accessories data sheet where a complete list and documentation can be found for accessories, or refer to the Connection Solutions catalog.

Chassis Compatibility

This PXI module must be used in a suitable chassis. It is compatible with the following chassis types:

- All chassis conforming to the 3U PXI and 3U Compact PCI (cPCI) specification
- Legacy and Hybrid Peripheral slots in a 3U PXI Express (PXIe) chassis
- Pickering Interfaces LXI or LXI/USB Modular Chassis



Chassis Selection Guide

Standard PXI or hybrid PXIe Chassis from any Vendor:

- Mix our 1000+ PXI switching & simulation modules with any vendor's PXI instrumentation
- Embedded or remote Windows PC control
- Real-time Operating System Support
- High data bandwidths, especially with PXI Express
- Integrated module timing and synchronization




Pickering LXI or LXI/USB Modular Chassis—only accept our 1000+ PXI Switching & Simulation Modules:

- Ethernet or USB control enables remote operation
- Low-cost control from practically any controller
- LXI provides manual control via Web browsers
- Driverless software support
- Power sequencing immunity
- Ethernet provides chassis/controller voltage isolation
- Independence from Windows operating system



Connectivity Solutions


We provide a full range of supporting cable and connector solutions for all our switching products—20 connector families with 1200+ products. We offer everything from simple mating connectors to complex cables assemblies and terminal blocks. All assemblies are manufactured by Pickering and are guaranteed to mechanically and electrically mate to our modules.



Connectors & Backshells



Multiwire Cable Assemblies



RF Cable Assemblies



Connector Blocks

We also offer customized cabling and have a free online Cable Design Tool that can be used to create custom cable solutions for many applications.

Mass Interconnect

We recommend the use of a mass interconnect solution when an Interchangeable Test Adapter (ITA) is required for a PXI or LXI based test system. Our modules are fully supported by both Virginia Panel and MacPanel.

Pickering Reed Relays

We are the only switch provider with in-house reed relay manufacturing capability via our sister company, Pickering Electronics. These instrument grade reed relays feature **SoftCenter®** technology, ensuring long service life and repeatable contact performance



Programming

Pickering provide kernel, IVI and VISA (NI & Keysight) drivers which are compatible with all Microsoft supported versions of Windows and popular older versions.

The VISA driver is also compatible with Real-Time Operating Systems such as LabVIEW RT. For other RTOS support contact Pickering. These drivers may be used with a variety of programming environments and applications including:

- **Pickering Interfaces Switch Path Manager**
- **National Instruments** products (LabVIEW, LabWindows/CVI, Switch Executive, MAX, TestStand, VeriStand, etc.)
- **Microsoft Visual Studio** products (Visual Basic, Visual C++)
- **Keysight VEE**
- **Mathworks Matlab**
- **Marvin ATEasy**
- **MTQ Testsolutions** Tecap Test & Measurement Suite

Drivers for popular Linux distributions are available, other environments are also supported, please contact Pickering with specific enquiries.

We provide Soft Front Panels (SFPs) for our products for familiarity and manual control, as well as comprehensive documentation and example programs to help you develop test routines with ease.

Signal Routing Software

Our signal routing software, Switch Path Manager, automatically selects and energizes switch paths through Pickering switching systems. Signal routing is performed by simply defining test system endpoints to be connected together, greatly accelerating Test System software development.



Diagnostic Relay Test Tools

eBIRST Switching System Test Tools are designed specifically for our PXI, PCI or LXI products, these tools simplify switching system fault-finding by quickly testing the system and graphically identifying the faulty relay.



Three Year Warranty & Guaranteed Long-Term Support

All standard products manufactured by Pickering Interfaces are warranted against defective materials and workmanship for a period of three years from the date of delivery to the original purchaser. Extended warranty and service agreements are available for all our modules and systems with various levels to suit your requirements. Although we offer a 3-year warranty as standard, we also include guaranteed long-term support—with a history of supporting our products for typically 15-20 years.

Available Product Resources

We have a large library of product resources including success stories, product and support videos, articles, as well as complete product catalogs and product reference maps to assist when looking for the switching, simulation and cable and connector solutions you need. We have also published handy reference books for the PXI and LXI standards.

