



**Smoke studies visualize airflow turbulence, balance airflow and locate dead airflow zones in cleanrooms, ISO suites, sterile rooms, medical rooms, barrier isolators, glove boxes, fume hoods, airflow hoods, bio-safety cabinets.**

Fogger Model	Fog Purity	Fog Volume	Fog Density	Fog Duration	Visual Airflow Distance	Liquids Used	Shipping Dimensions	Optional Accessories	Power
<b>CRF2 Cleanroom Fogger</b>	<b>Pure Fog</b> Low cost fogger solution for Semiconductor, Pharmaceutical & Medical	about <b>0.26 cubic meters / minute</b> for small barrier isolators, bio-safety cabinets, fume hoods, glove boxes <a href="#">WATCH CRF2 VIDEO</a>	about <b>57 ml fog density / minute</b>	about <b>50 minutes</b> , one 60mm fog output, refill and restart	about <b>7-8 feet visual airflow</b> , using one 60mm fog hose output	DI Water or WFI Water	CRF2 ships in box: 22 x 22 x 18 inches includes 3 accessories	22" Fog Curtain Wand, 10 ft. Remote Control Cable, Rolling Carry Case w/ Polyethylene foam Insert included with standard order	115 VAC 60 Hz, 220 VAC 50 Hz, 100VAC 50Hz
<b>CRF4 Cleanroom Fogger</b>	<b>Pure Fog</b> Medium fog volume solution for Semiconductor, Pharmaceutical & Medical	about <b>1.25 cubic meters / minute</b> for clean rooms, sterile rooms, medical rooms, ISO suites, barrier isolators <a href="#">WATCH CRF4 VIDEO</a>	about <b>187 ml fog density / minute</b> Adjustable fog volume and airflow velocity, optional wireless remote control	about <b>40 minutes</b> , one 80mm fog output, refill and restart	about <b>10-15 feet visual airflow</b> , using one 80mm fog hose output	DI Water or WFI Water	CRF4 ships in box, 30 x 21 x 18 inches Accessories are in additional boxes.	Optional Accessories: 1.3 Meter Fog Wand, Wireless Remote Control, CRF4 Rolling Carry Case w/ Polyethylene lining, Y & T Adaptor, 5 Meter Fog Hose, LED Fog Contrast Illuminator, 350mm Fog Nozzle, Accessory Rolling Carry Case w/ Foam Insert.	115 VAC 60 Hz, 220 VAC 50 Hz, 100VAC 50Hz
<b>AP35 LN2 Fogger</b>	<b>Ultrapure Fog</b> High fog volume solution for Semiconductor & Pharmaceutical	about <b>5 cubic meters / minute</b> for clean rooms, medical rooms, sterile rooms, ISO suites, large barrier isolators <a href="#">WATCH AP35 VIDEO</a>	about <b>571 ml fog density / minute</b> Adjustable fog volume and airflow velocity, optional wireless remote control	about <b>70 minutes</b> , one internal water heater and one 80mm fog output	about <b>20-30 feet visual airflow</b> , using one 80mm fog hose output	LN2 + (DI Water or WFI Water)	AP35 ships in crate: 1.2 M x 1 M x 0.8 M. Accessories are in additional boxes.	Optional Accessories: 1.3 M & 2 M Fog Wands, Wireless Remote Control, Accessory Rolling Carry Case w/ Foam Insert, Y & T Adaptor, 5 Meter Fog Hose, 350mm Fog Nozzle, LED Fog Contrast Illuminator, Spare LN2 Dewar	115 VAC 60 Hz, 220 VAC 50 Hz, 100VAC 50Hz
<b>AP100 LN2 Fogger</b>	<b>Ultrapure Fog</b> Highest fog volume solution for Semiconductor & Pharmaceutical	about <b>15.5 cubic meters / minute</b> for large clean rooms, sterile rooms, ISO suites	about <b>1520 ml fog density / minute</b> similar features as AP35	about <b>70 minutes</b> , two internal water heaters and four 80mm fog hose outputs	about <b>30-40 feet visual airflow</b> , using four 80mm fog hose outputs	LN2 + (DI Water or WFI Water)	AP100 ships in crate: 1.2 M x 1.2 M x 1.2M. Accessories are in additional boxes.	Optional Accessories: 1.3 M & 2 M Fog Wands, Wireless Remote Control, Accessory Rolling Carry Case w/ Foam Insert, Y & T Adaptor, 5 Meter Fog Hose, 350mm Fog Nozzle, LED Fog Contrast Illuminator, Spare LN2 Dewar	115 VAC 60 Hz, 220 VAC 50 Hz, 100VAC 50Hz
<b>Other LN2 Foggers</b>	<b>Ultrapure Fog</b> Medium fog volume solution for Semiconductor, Pharmaceutical & Medical	from <b>0.75 to 1.5 cubic meters / minute</b>	from <b>150ml to 250ml fog density / minute</b>	from <b>30-40 minutes</b> , one fog output	from <b>8-15 feet visual airflow</b>	LN2 + (DI Water or WFI Water)		Optional Accessories	115 VAC 60 Hz, 220 VAC 50 Hz, 100VAC 50Hz

